

## Technical Information Forestry Marking Spray Neon

---



Distein Forestry Marking Spray is to be used for marking of trees, wood and stone also. Distein Forestry Marking Spray with its reliable adhesion on wet surfaces is weather- and water-proof.

**The 360° valve enables to spray the forestry marking paint in all sites and directions, because of the special valve there is also a finer lettering possible.**

### Quality and properties

---

- Weather-proof, good adhesion on wet surfaces
- Ideal opacity and fluorescence
- Markings remain strongly visible from 2 to 3 years
- Frost-proof till -20° C
- Minimal drizzle
- 360° valve for marking in all sites and directions
- The special nozzle is perfect for flat spraying and wood marking
- High fertility
- Environment-neutral propellant, without CFC
- Without Toluene
- Without cadmium, lead and other heavy metal
- Easy colour-recognition with patented coloured donut
- Application is possible with metal spray handle

### Physical and chemical data

---

- **Colours:**  
Neon-red, Neon-orange, Neon-yellow, Neon-blue, Neon-green
- **Binder:**  
Acrylat
- Depending on surface and colour 500 ml are sufficient for approx. 3-4 m²
- **Drying:**  
Dust-dry: after 10 minutes  
Dry to touch: after 30 minutes  
Fully dried: after 24 hours
- **Disposal:**  
Only the completely empty can should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".
- **Storage stability:**  
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Container:**  
Maximum nominal volume = 500 ml

### Environment and labelling

---

**Environmentally compatible:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

*Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.*

**Labelling:** All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals (GHS)** or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

### Using Instructions

---

**Before use, carefully read and observe the warning texts on the label!**

- Before use, shake can well for 2 minutes.
- Spray to test colour and compatibility on an inconspicuous area.
- Distance approx 10-15 cm

### Order information

---

### Disclaimer of liability

---

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of November 07, 2014

This release replaces all eventually earlier issued versions.

Print date: 29.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)