

Technical Information Acrylic 2in1 Paint



DUPLI-COLOR acrylic-based 2in1 paint is low-odour, water-dilutable, resistant and fast drying top coat. It enables paintings in the highest possible quality.

The Clear Lacquer in this series is high transparent and ideal suitable as gloss coat on already painted surfaces.

The paint is excellently suitable for all paintable surfaces like wood, metal, stone, plaster, rigid plastic, zinc etc. and bearing old coats.

Quality and properties

- Usable for indoor- and outdoor-applications
- Shock- and impact-resistant
- Water-dilutable
- Good adhesion
- Weather- und lightproof
- Breathable
- Colour stable

Physical and chemical data

- **Basis of the binder:** Acrylate dispersion on base of water
- **Colour:** miscellaneous
- **Smell:** neutral
- **Degree of gloss** (at measurement angle 60° acc. to DIN 67530): satin gloss and matt
- **Efficiency:**
 - per 125 ml can: approx. 1,5 m²
 - per 250 ml can: approx. 3 m²
 - per 750 ml can: approx. 9 m²
- **Drying time (at 20°C, 65% relative air humidity):**
 - Dust-dry: after 3-4 hours
 - Coatable after 12 hours
 - The drying time depends on surrounding temperature, air humidity and absorptivity of the ground.
- **Best working temperature and object temperature:**
 - Object temperature min. +5°C
- **Cleaning of tools:** immediately after use with warm water and if necessary with a cleaner?
- **Storage stability:**
 - 5 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%) in the unopened original container.
 - Do not store below 5°C
- **Size:** metal tins 125 ml, 250 ml and 750 ml

Environment and labelling

Environmentally compatible: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using instructions

Before use, carefully read and observe the warning texts on the label!

Preparation of the ground:

- The surface has to be dry, clean and free from fat and rust.
- Remove old flaking paintings which are not bearing.
- Sand surface and prime with DUPLI-COLOR Aqua Universal Primer, rough wood with wood impregnating ground and metal with Rust Protection Primer.

Painting:

- Before application, always carefully stir up the paint
- Temperature of the object and surrounding temperature should be at least +??°C
- Working with brush, roll or airless spray
- Apply 1-2 final coats depending on wear.

Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not

exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of March 23, 2018

This release replaces all eventually earlier issued versions.

Print date: 03.05.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com