

Technical Information Window Shutter Oil



DUPLI-COLOR Fensterladenöl is suitable for window shutters, garage doors, front doors, wood construction in inside and outside premises.

It can only be used on not covering paintings and open-porous surfaces.

Quality and properties

- Aqueous oil-base
- With deep effect
- Water-repellent
- Colourless protective and care oil
- Breathable
- Non-resinous

Physical and chemical data

- **Basis of the binder:** aqueous oil-base
- **Colour:** transparent
- **Degree of gloss** (at measurement angle 60° acc. to DIN 67530): not relevant
- **Efficiency:** per 750 ml can: 9 - 12 m²
- **Drying time (at 20°C, 65% relative air humidity):**
Coatable after 1 - 4 hours
The drying time depends on surrounding temperature, air humidity and absorptivity of the wooden ground.
- **Storage stability:**
5 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%) in the unopened original container.
Use up material in the opened container within 6 months.
Do not store below 5°C.
- **Size:** metal tins 750 ml

Environment and labelling

Environmentally compatible: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using instructions

Before use, carefully read and observe the warning texts on the label!

- Substrates have to be bearing, clean, dry, must be fat- and waxfree and sanded as well as free from closed paint films.
- Object and oil temperature from +10°C to +25°C.
- Do not work in the direct sun.
- Test by a specimen paint-coat the colour and compatibility with the ground.
- Stir up well before and during use.
- Apply in 2 working steps this window shutter oil with a brush (natural bristles) in direction of the grain.
- Remove excess oil from the area with a clean cloth.
- Clean the tools with warm water and dishwashing detergent.

Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of March 13, 2018

This release replaces all eventually earlier issued versions.

Print date: 01.05.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com