

## Technical Information Tuning Alu Wheel Paint




For lacquering and repair works in the most current aluminium shades, especially for alloy rims

Optimal adhesion of the lacquer you'll achieve by using DUPLI-COLOR Primer before lacquering.

To protect the metal pigments in the lacquer, we recommend to seal the metallic lacquer with DUPLI-COLOR Tuning Wheel Paint Clear Coat art.no. 191671.

### Order informations

| Color                                                                             | Product                     | Bundle | Art.No. |
|-----------------------------------------------------------------------------------|-----------------------------|--------|---------|
|  | ALU WHEEL PAINT arctic 150  | 150 ml | 665615  |
|  | ALU WHEEL PAINT argento 12  | 12 ml  | 665653  |
|  | ALU WHEEL PAINT argento 150 | 150 ml | 665585  |
|  | ALU WHEEL PAINT artic 12    | 12 ml  | 665677  |
|  | ALU WHEEL PAINT quartz 12   | 12 ml  | 665691  |
|  | ALU WHEEL PAINT quartz 150  | 150 ml | 665646  |
|  | ALU WHEEL PAINT viper 12    | 12 ml  | 665660  |
|  | ALU WHEEL PAINT viper 150   | 150 ml | 665592  |

### Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of April 17, 2015

This release replaces all eventually earlier issued versions.

Print date: 02.05.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)