

Technical Data Sheet UV Marker



Distein UV Marker is a transparent Spray which you can use for marking surfaces, which should be invisible. You can't see the Spray by daylight, but with UV light.

Suitable for glazed, rough or primed surfaces like timber, metal, varnished plastics, carton, walls, machinery, etc.

Quality and properties

- weather-proof, good adhesion on wet surfaces and direct insolation
- transparent
- frost-proof till -10°C
- environment-neutral propellant, without CFC
- without toluene
- without cadmium, lead and other heavy metal
- invisible in daylight

Physical and chemical data

- **Color:**
daylight:transparent UV Light:blue
- **Efficiency:**
Depending on surface and color 400ml are sufficient for approx. 2-3m²
- **Drying:**
Dust-dry:after 20 minutes
Dry to touch:after 30 minutes
Fully dried:after 24 hours
- **Storage stability:**
5 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)

Environment and labelling

Environmentally compatible: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using Instructions

Before use, carefully read and observe the warning texts on the label!

- Before use, shake can well for 2 minutes.
- Spray to test colour and compatibility on an inconspicuous area.
- Distance approx 10-15 cm

Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of October 29,2012

This release replaces all eventually earlier issued versions.

Print date: 27.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com