

## Technical information Guide Coat Black



ColorMatic guide coat black is a high-quality acrylic paint that dries fast and is used to detect pores, cracks, uneven areas and sanding marks after application of putty or filler. The very fine atomization guarantees even application and reliable results.

### Application:

The ideal assistant for perfect sanding following putty and filler application.

## Quality and properties

- High-quality acrylic coat
- Fast drying time
- Useful for identifying pores, cracks and sanding marks
- Very fine atomisation ensures reliable results

## Physical and chemical data

- **Basis of binder:** Acrylic
- **Colour:** black
- **Smell:** solvent
- **Substrate:**  
very good dried and polished putties, primer or filler areas
- **Temperature resistance:** to 80°C
- **Storage stability:**  
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**  
Aerosol cans, maximum nominal volume 400 ml
- **VOC-value:** 257,5g

## Environment and labelling

**Environmentally compatible:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

*Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.*

**Labelling:** All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

## Using instructions

**Before use, carefully read and observe the warning texts on the label!**


- No special preparation required before applying ColorMatic guide coat black
- Shake the can well for 2 minutes
- Carry out spray test
- When using dark fillers/ primer fillers, we recommend using ColorMatic primer filler HG1, No. 856 532, know as guide coat white
- **For professional use only**
- **Wear an appropriate respirator (recommended type A2/P3)**



2 min



1



grindable 2-3 min

## Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of July 26, 2010

This release replaces all eventually earlier issued versions.

Print date: 02.05.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)

