

## Technical Information Structure Spray



DUPLI-COLOR Structure Spray creates an individual surface structure, similar to a rough plaster. It is an exclusive, water-based polyurethane dispersion, which is suitable to repair and adapt a textured plastering. It can be used on misc. surfaces, such as concrete, gypsum plasterboard, sheetrock, wood etc. Can be overcoated with all dispersion paints.

### Quality and properties

- bright white colour
- easy to apply
- good coverage
- fast-drying
- excellent adhesion
- repaintable with common wall paints
- for inside use

### Physical and chemical data

- **Basis of the binder:** polyurethane dispersion
- **Colour:** white
- **Efficiency:**  
500 ml are sufficient for approx. 1 m<sup>2</sup>
- **Drying time (at 21°C, 45 % relative air humidity):**  
repaintable after 2 hours  
The drying time depends on surrounding temperature, air humidity and absorptivity of the ground.
- **Storage stability:**  
2 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)  
Do not store below 5°C
- **Size:** 500 ml aerosol can

### Environment and labelling

**Environmentally compatible:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

*Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.*

**Labelling:** All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals (GHS)** or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

### Using instructions

**Before use, carefully read and observe the warning texts on the label!**

- If there are water stains, smoke or grime spots, we recommend to use first DUPLI-COLOR Blocking Primer.
- The surface has to be dry, clean, free from fat and wax as well as sanded.
- Shake can vigorously for 3 minutes and test spray on a carton or a wooden plate.
- Spray from a distance of approx. 25-30 cm.
- Spray in circular, permanent movements.
- Let dry.
- In order to achieve a thicker structure, spray again and let the spot dry.
- Turn can after use upside-down and spray several seconds, in order to clean the valve.

### Order information

### Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of April 13, 2018  
This release replaces all eventually earlier issued versions.

Print date: 27.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)