

Technical Information Blocking Primer



DUPLI-COLOR Blocking Primer to isolate soilings, for example water spots, to bind humidity on mineral grounds, e.g. plaster, concrete, in cellars, garages, on facades, walls etc. in interior and exterior premises. Helps to avoid saline bloom.

Suitable for water spots, carbon black and efflorescence.

Quality and properties

- covering white
- ties humidity
- adheres even on humid subsoils
- for inside and outside
- can be used above and below the ground earth
- containing concrete
- alkali-proof and mould-resistant
- ease of use
- high coverage
- low smell

Physical and chemical data

- **Basis of the binder:** modifiziertes Acrylharz
- **Colour:** white
- **Degree of gloss** (at measurement angle 60° acc. to DIN 67530): satin matt
- **Efficiency:** approx. 4 - 6 m² per litre
- **Drying time (at 20°C, 65% relative air humidity):**
dust-dry after approx. 2,5 hours
fully dried after approx. 24 hours
The drying time depends on surrounding temperature, air humidity and absorptivity of the ground. Excessive layer thickness and missing air movement can delay the drying time.
- **Cleaning of tools:** immediately after use with white spirit
- **Storage stability:**
2 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%) in the unopened original container.
Do not store below 5°C
- **Size:** 750 ml metal tin

Environment and labelling

Environmentally compatible: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using instructions

Before use, carefully read and observe the warning texts on the label!

- Remove food during the working and drying time from the concerned rooms.
- Ground may be slightly humid, but it must be clean and bearing.
- Not suitable for sandstone.
- In case of durable impact of humidity the source has to be eliminated before.
- Stir well.
- Apply 1 - 2 times, the first application with a brush.
- Further coatings with a brush or roller.
- Working temperature: +8°C - +25°C.

Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of March 21, 2018

This release replaces all eventually earlier issued versions.

Print date: 30.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com