

Technical Information Light Filler



presto Light Filler "styrene-free" has, due to the use of novel fillers, a density lower than 1 kg / dm³. That means, that the weight of the Light Filler is only half as high as conventional fillers. Therefore you can use it on objects, which shall not be loaded with high weight.

Typical applications:

- car bodies, even made of plastic
- re-working of weld seams and folds
- in boat building, during repair of boats and surfboards
- in model making or
- to repair powder coatings

For preparation and finishing your filling job, we recommend our presto sand papers. We offer a wide assortment of fine and coarse papers for dry and wet sanding.

Order informations

Color	Product	Bundle	Art.No.
	presto SF Leichtspachtel 125g	125 g	443718
	presto SF Leichtspachtel 420g	420 g	443725

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of March 8, 2016

This release replaces all eventually earlier issued versions.

Print date: 29.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com