

Technical information Guide Coat Black



ColorMatic Quick Check spray for checking sanded surfaces to identify irregularities. Produces a temporary gloss which evaporates residue-free. Also useable for the checking the color of spray samples.

Application:

The ideal assistant for perfect sanding following clear coat application.

Quality and properties

- Sprays gloss in a matter of seconds
- Evaporates residue-free
- Useful for identifying smallest dents and irregularities
- Produces colorfast spray samples
- Easy to use
- Ensures perfect results

Physical and chemical data

- **Basis of binder:** Aliphatic hydrocarbons
- **Colour:** transparent
- **Smell:** solvent
- **Substrate:**
sanded primer or filler areas
- **Storage stability:**
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**
Aerosol cans, maximum nominal volume 400 ml
- **VOC-value:** 276,0g

Environment and labelling

Environmentally compatible: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".


Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using instructions

Before use, carefully read and observe the warning texts on the label!

- No special preparation required before applying ColorMatic Quick Check spray
- Shake the can for 5 seconds
- Surface check: Apply ColorMatic Quick Check in 1-2 thin layers. Rub with a paper tissue until an even surface film is arising
- Color check: Apply ColorMatic Quick Check on the basecoat lacquered spray sample and also on the car part which is for comparison
- After 20 minutes (depends on ambient temperature) the film is residue-free evaporated
- Tolerability testing is needed
- **For professional use only**
- **Wear an appropriate respirator (recommended type A2/P3)**



Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of November 7, 2018

This release replaces all eventually earlier issued versions.

Print date: 28.04.2024

European Aerosols GmbH | Kurt-Vogelmann-Straße 8 | 74855 Heilbronn | info.de@european-aerosols.com

