

Technical Information Silicone Remover



DUPLI-COLOR Silicone Remover is essential for professional paintwork results because it thoroughly removes dirt, grease, oil, silicone, wax, tar, adhesive residues etc. DUPLI-COLOR Silicone Remover saves a great deal of time because it is quick and easy to use and universally applicable. It enhances adhesion for subsequent coatings.

Application:

Ideal for spot repairs and refinishing parts, as well as all work that requires a professional clean.

Qualities and Properties

- Simple, time-saving application
- Thorough removal of silicone, grease, oil, wax, dirt, tar, adhesive residues etc.
- Mild, non-aggressive solvent
- Improves adhesion of subsequent coatings
- Extremely time saving

Physical and chemical data

- **Colour:** transparent
- **Smell:** solvent
- **Efficiency:** very good
- **Substrate:** primed and filled areas
metal, glass
old paints and original paints from supplier
painted and unpainted surfaces
- **Storage:** 24 month if appropriate storage provided
- **Size:** Aerosol cans, maximum nominal volume 150 ml
- **VOC-value:** 269,7g

Environment and labelling

Environmentally compatible: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using instructions

Before use, carefully read and observe the warning texts on the label!

Instructions:

- Shake the can shortly before use
- 1 - 2 light coats, repeat if dirt excessive
- Wipe off with a clean, dry, non-woven cloth
- Allow cleaned surfaces to dry
- Suitable for all levelled, primed and filled surfaces
- Suitable for metal and glass
- Suitable for old and original paintwork
- Suitable for painted and unpainted undercoats

Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of June 26, 2013

This release replaces all eventually earlier issued versions.

Print date: 04.05.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com