

Technical Information MD 100 Multi-Spray



presto MD 100 Multi-Functional Spray is a high-quality, all-purpose oil for lubricating and protecting metal and rubber parts. Loosens tight screws and removes oil, tar, wax and residues of glue. It is perfect for all types of maintenance at home and in the workshop.

NOW NEW: With innovative <u>DUAL-SPRAY spray head</u> - this enables both a wide, flat and a precise spray and thus offers even more flexibility!

For use on:

Locks, garden tools, gears, pedals, tools, fittings, home trainers

Quality and properties

- Good penetration
- Moisture repellent
- Cleaning effect
- Removes oil, wax, Tectyl and tar
- · Good corrosion protection
- Excellent adhesion
- Leaves no residue
- · Non-corrosive
- Non-conductive
- Non-conductive
 Powerful degreaser
- Silicone-free
- · Directed jet spray
- TRG 300 compliant

Physical and chemical data

• Basis: mineral oil

• Colour: brownish

• Smell: Vanillla

• Relative density at 20°C: 0.80 g/ml

Yield: 1.98 g/sec.

• Vapour pressure at 20°C: 3 - 4 bar

• Temperature resistance: -50°C to +200°C

Storage stability:

10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)

Size:

aerosol can, maximum nominal volume 400 ml

Environment and labelling

Environmentally compatible: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using instructions

Before use, carefully read and observe the warning texts on the label!

Application:

- · Bring can to room temperature.
- Operating temperature 5° to 30°C.
- Shake can for 2 minutes before use.
- · Spray a thin coat and flash off. Optimum lubrication occurs once the solvent has evaporated.
- After cleaning, an invisible protective film appears.

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of: March 12, 2014

This release replaces all eventually earlier issued versions.

Print date: 29.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com