

Technical Information Vignettes Remover Kit



Complete set for quick and easy removal of vignettes, environmental stickers / fine dust stickers, stickers and adhesive residue such as of window films. Removes them gently and residue-free from glass surfaces.

Content: Remover Spray 50ml, scraper with metal blade, sponge, cloth

Quality and properties

- Complete set includes everything you need to remove
- Fast and easy application
- Residue-free removal

Physical and chemical data

Basis: D-LimonenColour: transparent

Smell: Citrus

Relative density at 20°C: 0.84 g/ml
Vapour pressure at 20°C: 3.5 bar
Refractive index at 20°C: 1.385
Propellant:: Propan / Butan

· Storage stability:

10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)

· Size:

aerosol can, maximum nominal volume 50 ml

Environment and labelling

Environmentally compatible: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using instructions

Before use, carefully read and observe the warning texts on the label!

Application:

- · Bring can to room temperature.
- Operating temperature 5° to 30°C.
- Shake can for 2 minutes before use and test surface compatibility.
- . Spray evenly on the vignette and allow to soak.
- Collect excess fluid with enclosed sponge.
- Then remove Vignette careful with the scraper (Caution with sensitive surfaces).
- Spray again to loosen any existing adhesive residues.
- · Wipe clean treated area with the supplied cloth

Order informations

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of October 9, 2015

This release replaces all eventually earlier issued versions

Print date: 30.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com