

Technical Information Tyre repair



Rubber based spray to execute emergency repairs on tubeless tyres. Can be used without removing the tyre. Immediate roadside assistance. Closes in seconds holes in the tire and pumped it up again.

Suitable for all common types of tires up to max. 18 inches.

Quality and properties

- First Aid for flat tires
- Using without demounting the tyre
- Seals and pumps on again
- User-friendly
- Rubber-based

Physical and chemical data

- **VOC-Content:** Approximately 50% w/w
- **Storage stability:** 10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:** aerosol can, maximum nominal volume 500 ml

Environment and labelling

Environmentally compatible: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Instruction manuel

Before use, carefully read and observe the warning texts on the label!

Application:

- Bring the can to room temperature / Operational temperature 5 to 30°C.
- Shake before use.
- Search the cause of the leakage and remove this.
- Completely let the tyre down.
- Screw the adaptor on the valve.
- Hold the can upside down and empty completely.
- Drive approximately ten (10) kilometres with a maximum speed of 50 kilometre per hour in order to enable the product to equally spread in the tyre.
- Then remove the propellant from the tyre and again bring the tyre on pressure.
- Note: presto tyre repair is a breakdown help. Repair the tyre soonest, indicating the tyre was temporarily repaired with Tyre Repair. Suitable to repair small leakages in the tread of the tyre.

Order informations

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of: January 10, 2014

This release replaces all eventually earlier issued versions.

Print date: 29.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com