

## Technical Information Alkyton heat-resistant brush paint



Universal thinner for all Alkyton lacquers to brush, roll and especially to apply with a spray gun.

Also excellently suitable as degreaser and as cleaning agent for metals: removes paint splatters and stains.

### Quality and properties

- Thinner for all Alkyton lacquers as well as other solvent-containing synthetic or chlorinated rubber paints.
- Slowly evaporating thinner for perfect paint coats
- Excellent cleaning power: removes paint splatters and colour stains.
- Do not use on synthetic material and painted surfaces!

### Physical and chemical data

- **Form:** fluid
- **Colour:** clear, colourless
- **Smell:** solvent, characteristic
- **Boiling point:** 70-230°C
- **Flash Point:** >21°C
- **Density:** 0,798 g/cm³
- **Storage stability:**  
5 years from date of production in unopen can, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.
- **Disposal:** Put only empty can into the recycling bin. Bring cans with remainders of paint to the special refuse disposal.
- **Content:** 500 ml can

### Environment and labelling

**Environmentally compatible:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

*Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.*

**Labelling:** All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

### Using instructions

**Before use, carefully read and observe the warning texts on the label!**

As cleaner: to clean up tools, paint splatters etc.

**As thinner** for Alkyton lacquers we recommend for application with:

- Brush: Up to 10 vol. % synthetic thinner; use natural bristles, long hair brushes.
- Roller: Up to 10 vol % synthetic thinner; use short nap, polyamide (Perlon) 6 – 12 mm rollers. Roller application may require 2 coats to achieve recommended dry film thickness.
- Spraygun: 10 - 25 vol. %: synthetic thinner  
Gravity cup and pressure cup. Tip size: 1,0 - 1,5 mm.  
Atomising pressure: 2 - 4 bar.

### Order information

#### Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of: 5th February 2014

This version replaces all eventually earlier issued versions.

Print date: 29.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)