

## Technical Information Tar Spray



Lubricant and preservative on basis of Stockholm tar to prevent wear and sticking of screwed connections which are liable to heavy workload. Tar Spray gives lasting protection, is water-repellent and resistant to weather influences and weak acids and bases. MoTip Tar Spray has excellent adhesion and excellent corrosion prevention.

•

### Quality and properties

- Lasting protection
- Water-repellent
- Excellent adhesion
- Prevents wear and sticking
- Resistant to weather influences
- Resistant to weak acids and bases
- Excellent corrosion prevention
- Directed jetspray
- 360° Valve

### Physical and chemical data

- **Basis:** Stockholm Tar
- **VOC-content:** approximately 75% w/w
- **Colour:** transparent brown
- **Smell:** characteristic
- **Relative density at 20°C:** 0.76 g/ml
- **Yield:** 1 - 1,5 g/sec
- **Temperature resistant:** -30 to + 180 °C
- **Vapour pressure at 20°C:** 3 - 4 bar
- **Size:**  
aerosol can, maximum nominal volume 500 ml

### Environment and labelling

**Environmentally compatible:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

*Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.*

**Labelling:** All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

### Instruction manuel

**Before use, carefully read and observe the warning texts on the label!**

#### Application:

- Bring can to room temperature.
- Operating temperature 5° to 30° C.
- Shake for 2 minutes before use.
- Spray parts to be treated prior to assembly. After evaporation a protective film remains, which simplifies the futur disassembly.
- The protective film can be removed with MoTip Industrial Cleaner.

### Tips for spray painting

Protect the object and the surrounding area from spray mist.  
Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

### Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of: October 01, 2014

This release replaces all eventually earlier issued versions.

Print date: 29.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)