

## Technical Information 2K Garage Floor Paint



DUPLI-COLOR 2K Garage Floor Paint is a seal coat for protection and decoration of concrete floor surfaces exposed to moderate, medium heavy mechanical and chemical wear, e.g. garages, laboratories, warehouses, production facilities. Protection of wall surfaces that are exposed to moisture, chemicals and stronger chemical loads. It can be used for protection and decoration of walls and floors covered with ceramic tiles.

### Quality and properties

- water-dilutable
- no intense odour
- dry film is resistant to abrasion and resistant to the effects of water and chemicals
- excellent adhesion the substrate
- easy to clean and maintain by washing
- has a short curing time
- creates a barrier to CO<sub>2</sub>

### Physical and chemical data

- **Basis of the binder:** epoxy-coating, water-thinnable
- **Smell:** neutral
- **Efficiency:**  
Depending on thickness of layer  
6 kg are sufficient von 15m<sup>2</sup>
- **Drying time (at 20°C, 65% relative air humidity):**  
dust-dry: after 6-8 hours  
walkable (for pedestrians): after approx. 24 hours  
fully hardened: after 7 days  
The drying time depends on surrounding temperature, air humidity and absorptivity of the ground.
- **Cleaning of tools:** immediately after use with water
- **Storage stability:**  
2 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%) in the unopened original container.  
Do not store below 5°C and over 25°C.
- **Size:** 6 kg tin containers (component A = 4,8 kg and component B (hardener) = 1,2 kg)

### Environment and labelling

**Environmentally compatible:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

*Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.*

**Labelling:** All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

### Using instructions

**Before use, carefully read and observe the warning texts on the label!**

- Stir well the component A.
- After that give the component B to the component A and mix it with an electric stirring gear at low speed (max. 400 turns/min.)
- Smaller quantities can be mixed manually.
- Give little by little water (approx. 5-10% on the mixture) into the homogenous mixture.
- For thoroughly mixing, fill the mixture into another container and mix it again well.
- Mixing ratio (per cent by weight): component A : component B 80 : 20 (100 : 25)
- Pot life: 90 min. at standard conditions.
- Apply with a short-haired roller or by spraying (airless device)

### Order information

### Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of September 7, 2018

This release replaces all eventually earlier issued versions.

Print date: 29.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)