

Technical Information Interior Dispersion



DUPLI-COLOR Interior Dispersion is the simple white for uncritical paintings at a favourable price. It shows after the drying process it's good coverage.

For simple paintings in the interior as well as in cellar rooms, garages, storerooms. Suitable for light / only slightly soiled substrates.

Quality and properties

- Good coverage after drying
- white - satinmatt
- poor in bad odour
- limited cleanability
- can be tinted with mixing colours

Physical and chemical data

- **Basis of the binder:** synthetic dispersion
- **Colour:** white
- **Smell:** neutral
- **Degree of gloss** (at measurement angle 60° acc. to DIN 67530): satin matt
- **Efficiency:**
approx. 10 litre are sufficient
wood chip wall paper white coated - 55 m²
wood chip wall paper uncoated - 45 m²
Smooth plaster - white coated - 65 m²
Smooth plaster - uncoated - 45 m²
Rough plaster - white coated - 45 m²
Rough plaster - uncoated - 35 m²
- **Drying time (at 20°C, 65% relative air humidity):**
surface dry after approx. 4-6 hours
re-coatable after approx. 8 hours
The drying time depends on surrounding temperature, air humidity and absorptivity of the ground.
- **Best working temperature and object temperature:**
Object and working temperature should not be below 5°C.
- **Cleaning of tools:** immediately after use with water
- **Storage stability:**
2 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%) in the unopened original container.
Store frost-free
- **Size:** 10 litre plastic buckets

Environment and labelling

Environmentally compatible: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using instructions

Before use, carefully read and observe the warning texts on the label!

Before coating:

- Cover floors and furniture with a foil.
- Mask off windows and door frames with a masking tape.
- Test the subsoil - it must be firm, dry, clean and stable.
- In case it changes colour to dark during the test with a humid sponge, a primer is necessary.
- Old paintings of glue-bound distemper and chalking surfaces must be completely washed off.
- If necessary, prime with a deep ground.

Coating:

- The colour is ready-to-use and has only to be stirred up carefully.
- It should not be worked if object and working temperatures are below 5°C.
- Can be brushed, rolled or sprayed airless.
- Paint first the ceiling, then the walls.
- In order to avoid visible edges, begin at the window and brush away from the light.
- Work on connected areas without break as a whole.
- In working breaks wrap brush and roller tightly with a plastic foil.
- After work, clean the tools with warm water.
- This colour can be overcoated after 8 hours.

Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of February 8, 2018

This release replaces all eventually earlier issued versions.

Print date: 02.05.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com