

Technical Information Tuning Wheel Paint clear lacquer



The quick, easy and durably gloss-coating and sealing for steel wheels and alloy rims.

The optimal varnish coating for [DUPLI-COLOR Tuning Wheel Paint](#).

Quality and Properties

- High-grade acrylic quality
- Excellent adhesion
- Good flow, smooth surface
- Excellent gloss retention
- Very hard surface, good elasticity
- Quick-drying
- Light-proof, UV-resistant (non-yellowing)
- Weather- and dirt-resistant
- Scratch-, shock- and impact-resistant
- After drying resistant against water, diluted acids and bases
- Limited resistance against petrol

Physical and Chemical Data

- **Basis of the binder:** Acrylate copolymers
- **Colour:** transparent
- **Smell:** solvent
- **Degree of gloss** (at measurement angle 60° acc. to DIN 67530): glossy: 80 - 90 gloss units
- **Efficiency:**
Depending on consistence and color of the ground:
400 ml are sufficient for 4 wheels
- **Drying time (at 20°C, 50% relative air humidity):**
Dust-dry: after approx. 15 minutes
Dry to touch: after approx. 30 minutes
Cured, can be polished: after approx. 24 hours
The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.
- **Temperature-resistant:** up to 80°C
- **Storage stability:**
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:** aerosol cans, maximum nominal volume 400 ml

Environment and labelling

Environmentally compatible: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using instructions

The most DUPLI-COLOR spray paints have a so-called no-spray ring or a tamper-proof cap. This is to avoid unauthorized use. Please see the corresponding advises on the cap or on the label.

Before use, carefully read and observe the warning texts on the label!

Application

- Remove rust and dirt.
- Eventually apply DUPLI-COLOR Tuning Wheel Paint silver or gold; please attend the instructions on the can or in the referring Technical Data Sheet.
- The ground has to be clean, dry and free from fat.
- Cover areas not to be painted.
- Before use, shake can for 3 minutes.
- Test spray at an invisible spot.
- Spray from a distance of 25 cm several thin cross-coats of the clear lacquer.
- Do not spray over surfaces which are painted with synthetic resin lacquer!

Tips for spray painting

Protect the object and the surrounding area from spray mist. When painting small areas it is recommended that a piece of card is used as a mask, with a hole cut in it slightly larger than the area to be sprayed. The mask should be held 1 to 2 cm from the surface. With this method, the mainly part of the spray mist is brought under control. It recommends to mask parts not to be lacquered, to protect the surrounding against the spray mist.

The aerosol can should have room temperature.

Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of December 1, 2009

This release replaces all eventually earlier issued versions.

Print date: 29.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com