

Technical Information Self Fusion Tape



Vulcanising tape that forms a homogeneous mass after application, without the need for heat or pressure.

Quality and properties

- Suitable for insulating electric cables, sealing hoses etc.
- For temporary and permanent repairs

Physical and chemical data

- **Carrier:** PIB rubber
- **Maximum temperature:** 90°C
- **Tensile strength:** 2 mPa
- **Thickness:** 0,50 mm
- **Breakdown voltage:** 21 kV

Using instructions

The most DUPLI-COLOR spray paints have a so-called no-spray ring or a tamper-proof cap. This is to avoid unauthorized use. Please see the corresponding advises on the cap or on the label.

Before use, carefully read and observe the warning texts on the label!

Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of August 14, 2014

This release replaces all eventually earlier issued versions.

Print date: 03.05.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com