

## Technical Information Insulation Tape 52100

---



Suitable for electrical insulation and for strengthening, protecting and repairing. Maximum temperature: 90°C.

### Quality and properties

---

- Flame retardant
- Easily removable

### Physical and chemical data

---

- **Adhesive:** rubber
- **Carrier:** PVC
- **Maximum temperature:** 90°C
- **Adhesive strength:** 5 N/ 25 mm
- **Thickness:** 0,15 mm
- **Breakdown voltage:** 6 kV

### Using instructions

---

Temperature: Between 0°C and +30°C.

Surface must be clean and free from dust and grease. Stored under appropriate conditions shelf life will be a minimum of 36 months.

### Order information

---

### Disclaimer of liability

---

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of August 14, 2014

This release replaces all eventually earlier issued versions.

Print date: 30.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)