

Technical Information Zinc Spray



Quality and properties

- High-grade nitro-combi quality
- Quick-drying
- Very good coverage
- Colour-matching
- Excellent adhesion on many surfaces
- Good flow, smooth Surface
- Suitable to paint and repair objects for inside and outside use

match of colour!)

- Surface can be polished
- Weather-resistant, light proof, UV-resistant
- Scratch-, bump- and shock-proof

Physical and chemical data

For all paintings and repairs in the shade grey, colour-matching in the surrounding field of metal surfaces (test

The application is possible on the most different surfaces. e.g metal, wood, glass, ceramics, stone, paper etc.

To repair or match the colour of zinc-plated surfaces please use MOTIP Zinc Alu Spray.

- Basis of the binder: nitro-combi
- Colour: grey
- Smell: solvent
- Degree of gloss (at measurement angle 60° acc. to DIN 67530): matt, 15 gloss units
- Efficiency:
- Depending on consistence and color of the ground: 400 ml are sufficient for approx. 1.0 - 2.0 m²
- Drying time (at 20°C, 50% relative air humidity): Dust-dry: after approx. 10 minutes Dry to touch: after approx. 30 minutes
 - Fully dry: after approx. 2 hours
 - Can be polished after approx. 24 hours The drying time depends on surrounding temperature, air
- humidity and thickness of the applied coat.
- Temperature resistant: up to 80°C
- Storage stability:
- 10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- Size:
- aerosol cans, maximum nominal volume 400 ml

Environment and labelling

Environmentally compatible: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Only for DE. In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Instruction manuel

The most MoTip spray paints have a so-called no-spray ring or a tamper-proof cap. This is to avoid unauthorized use. Please see the corresponding advisés on the cap or on the label.

Before use, carefully read and observe the warning texts on the label!

Application

- Remove rust and dirt
- · The ground has to be clean, dry and free of fat.
- Use a primer, if necessary.
 Cover areas not be painted.
- Before use, shake the can for approx. 2-3 minutes
 Test colour and compatibility of the spray and an invisible spot.
- Spray from a distance of approx 25 cm serveral thin cross-coats.
 Do not spray over synthetic-based paints!

Tips for spray painting

Protect the object and the surrounding area from spray mist. When painting small areas it is recommended that a piece of card is used as a mask, with a hole cut in it slightly larger than the area to be sprayed. The mask should be held 1 to 2 cm from the surface. With this method, the mainly part of the spray mist is brought under control. It recommends to mask parts not to be lacquered, to protect the surrounding against the spray mist.

The aerosol can should have room temperature.

Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to Européan Aerosols.

As of July 15, 2016 This release replaces all eventually earlier issued versions.

Print date: 29.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com