

## Technical Information Assembly Cleaner



presto assembly cleaner is a highly effective rapid cleaner for the maintenance, repair and installation of machinery, vehicles, precision mechanical and tools. It dissolves old and hardened oil and fat residues as well as remnants of brake fluid and silicone. The cleaner serves as pre and basic cleaning and degreases all sliding surfaces and parts prior to the application of special lubricants.

### Qualität und Eigenschaften

- High solvency power
- Leaves no residue
- Non-conductive
- Non-corrosive
- Removes tough oil and grease
- Powerful directed jet spray
- Can be sprayed from any angle due to a special 360 ° valve.
- Observe TRG 300

### Physical and chemical data

- **Basis:** Aliphaton
- **Colour:** transparent
- **Smell:** aliphatic
- **Density at 20°C:** 0,67 g/ml
- **Yield:** 3-4 g/sec.
- **Vapour pressure at 20°C:** 5,5 - 6,0 bar
- **Propellant:** carbon dioxide
- **Storage stability:**  
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**  
aerosol can, maximum nominal volume 500 ml

### Environment and labelling

**Environmentally compatible:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

*Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.*

**Labelling:** All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals (GHS)** or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

### Using instructions

**Before use, carefully read and observe the warning texts on the label!**

#### Application :

- Make sure can is at room temperature.
- Application temperature 5 ° to 30 ° C.
- Cover painted and plastic parts.
- Shake can well before use.
- Spray the parts to be treated until the dirt disappears.

### Order informations

### Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of December 17, 2009

This release replaces all eventually earlier issued versions.

Print date: 30.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)