

Technical Information Synthetic Adhesive Lube



presto Synthetic Adhesive Lube is a spray grease for lubrication of metal and plastics mechanical parts. By the excellent mechanical and thermal stability prevent wear and sticking of joints. The spray suppresses noises and provides good for corrosion.

Application areas:

joints, hinges, door locks, etc.

Quality and properties

- Prevents wear and sticking
- Excellent adhesion and creep power
- Suppresses noises
- High viscosity
- O-ring neutral, i.e. does not attack seals
- Good corrosion resistance
- Excellent mechanical and thermal stability
- Leaves a sticky surface
- Extremely weather resistant
- Resistant to salts, dilute acids and alkalis
- Water-repellent
- Contains PTFE
- Directed jetspray
- This product is equipped with a special cap. The cap contains a tube and a spray nozzle for directed application in inaccessible places.
- Attend the TRG 300

Physical and chemical data

- **Basis of the binder:** calcium-grease
- **Colour:** white
- **Relative density at 20°C:** 0,665 g/ml
- **Vapour pressure at 20°C:** 3 - 4 bar
- **Drop point:** 42°C to 60°C
- **Temperature resistance:** -30°C till +180°C
- **pH-value:** neutral
- **Storage stability:**
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**
aerosol cans, maximum nominal volume 400 ml

Environment and labelling

Environmentally compatible: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals (GHS)** or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using instructions

Before use, carefully read and observe the warning texts on the label!

Application

- The aerosol should have room temperature.
- Best processing temperature 5 to 30°C.
- Before application we recommend the cleaning with presto Assembly Cleaner.
- Shake can thoroughly before use.
- Synthetic Adhesive Lube apply on all parts which shall be treated.
- After the evaporation of the solvent a soft, extremely adhesive lubricant film develops.

Order informations

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of April 4, 2011

This release replaces all eventually earlier issued versions.

Print date: 01.05.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com