

Technical Information Wood Cleaner Anti-Grey



DUPLI-COLOR Wood Cleaner Anti-Grey is a ready-to-use cleaning agent for all greyed woods. Free from solvents and preserving agents.

Exemplary uses are chairs, benches, tables, fences, palisades, pergola, wooden decks, terraces, wooden facades, all woods that turned into grey from weather.

Quality and properties

- Low smell
- Free from solvents and preserving agents
- Ready-to-use

Physical and chemical data

- **Basis of the binder:** Water-based
- **Smell:** neutral
- **Degree of gloss** (at measurement angle 60° acc. to DIN 67530): not relevant
- **Efficiency:**
500 ml are sufficient for 4 m²
- **Drying time (at 20°C, 65% relative air humidity):**
Coatable after min. 48 hours
The drying time depends on surrounding temperature, air humidity and absorptivity of the wooden ground.
- **Storage stability:**
5 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
Do not store below 5°C
- **Size:** plastic container with 500 ml

Environment and labelling

Environmentally compatible: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using instructions

Before use, carefully read and observe the warning texts on the label!

- Remove rough and loose dirt.
- Wear protective gloves.
- Wet the wooden area you wish to work on.
- Cover generously areas which shall not be treated, especially metals or plants, for example with painters foil.
- Apply the Wood Cleaner richly with a sponge or a cloth and brush it in with a hard brush in direction of the fiber.
- After 15 minutes of reaction time remove the solved greying by using a hard brush or a non-woven web (no steel-wool) and plenty of water in direction of the fiber.
- Thoroughly let dry (at least 2 days during dry and warm weather).
- We recommend to protect the wood afterwards with a DUPLI-COLOR Wood Lasure.
- Clean the tools during and after work with water

Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of March 14, 2018

This release replaces all eventually earlier issued versions.

Print date: 29.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com