

Technical Information Repair putty



Superlight putty for easy patching and repairing of cracks and holes (drill and dowel holes) as well as for smoothing of smaller unevennesses in the indoor area.

Ready-to-use with high filling power, mouldable and very easy to smooth, hardens without shrinking or cracking, can be sanded and painted over.

For walls and ceilings made of plasterboard, concrete, plaster, woodchip, masonry, aerated concrete and polystyrene.

Quality and properties

- - Immediately ready for use
 - Hardens without cracking or shrinkage
 - Can be painted over
 - Fast drying
 - Easy application thanks to dosing tip
 - Drill and screw resistant
 - Smooth and flexible
 - Excellent adhesion

Physical and chemical data

- - **Chemical Basis:** Acrylic dispersion
 - **Form:** viscous paste
 - **Colour:** white
 - **Density:** approx. 0.53 g/l cm³
 - **Processing temperature:** between +10°C and 20°C. Do not use at temperatures below 7°C.
 - **Drying (at 20°C, 50% relative humidity):** Sandable/coatable after approx. 1-2 hours / 20°C. Completely dry after 24 hours / 20°C.
 - **Shelf life/storage:** 12 months in the unopened original packaging when stored in a cool and dry place (=5°-25°C, relative humidity of max. 60%). The storage temperature should not exceed 25°C for a longer period of time. Keep away from moisture, direct sunlight and heat sources.
 - **Container/contents:** Plastic tube with 225 ml content

Environment and labelling

Environmentally compatible: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using instructions

Before use, carefully read and observe the warning texts on the label!

Application

- Knead the tube well before use.
- The substrate must be free of dirt or loose particles before applying the filler.
- All separating substances must be completely removed.
- Painted surfaces must be cleaned and sanded.
- Apply the filler directly from the tube and smooth with a trowel blade.
- After drying (approx. 1 to 2 hours/ 20°C depending on layer thickness), the filler can be sanded and painted over.

Clean up

- Stains of material can easily be removed with water (before cure).

Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of: April 16, 2024
This release replaces all eventually earlier issued versions.

Print date: 06.05.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com