

Technical Information Premium White



DUPLI-COLOR Premium White: the premium dispersion paint with high degree of white and high coverage.

Quality and properties

- high degree of white
- highest coverage
- solvent-free
- wash-resistant
- breathable

Physical and chemical data

- **Basis of the binder:** acrylate-dispersion
- **Colour:** white
- **Smell:** neutral
- **Degree of gloss** (at measurement angle 60° acc. to DIN 67530): satin matt
- **Efficiency:** approx. 7 m² per litre
- **Drying time (at 20°C, 65% relative air humidity):** surface dry after approx. 2 hours
re-coatable after approx. 4 hours
The drying time depends on surrounding temperature, air humidity and absorptivity of the ground.
- **Best working temperature and object temperature:** Not less than 5°C.
- **Cleaning of tools:** immediately after use with water
- **Storage stability:** 2 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%) in the unopened original container.
Do not store below 5°C
- **Size:** 2.5 litre and 10 litre plastic buckets

Environment and labelling

Environmentally compatible: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using instructions

Before use, carefully read and observe the warning texts on the label!

Before coating:

- Cover floors and furniture with a foil.
- Mask off windows and door frames with a masking tape.
- Test the subsoil - it must be firm, dry, clean and stable.
- Remove completely loose old paintings, old paintings of glue-bound distemper and wallpapers.
- Prime repaired spots, absorbant and chalking grounds with a deep ground.

Coating:

- The colour is ready-to-use and has only to be stirred up carefully.
- Do not work with the colour if temperature is less than 5°C.
- Can be brushed, rolled or sprayed airless.
- Usually one rich and even paint coat is sufficient.
- In case of different, contrast-rich or different absorbant subsoils a previous paint coat, diluted with max 10 % water may be necessary.
- Paint first edges and corners with a brush or a small roller.
- Then paint the remaining bigger areas with a bigger roller.
- During working pauses wrap tightly brush or roller.
- After working clean the tools with water.
- This paint can be re-coated after 4 hours.

Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not

exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of March 26, 2018

This release replaces all eventually earlier issued versions.

Print date: 01.05.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com