

## Technical Data Sheet Line Protection



Particularly quick drying, transparency sealing varnish, especially developed for the assortment of COLORMARK Linemarker. The sealing varnish protects the color against dust and dirt, especially in areas with high mechanical pressure. Can be painted directly on the dry marked area with the known marking appliances Speedliner<sup>2</sup> / Speedliner<sup>2</sup> air. For inner area and outdoor. The subsoil has to be clean, dry, rustfree and greaseless.

### Quality and properties

- transparent protection layer
- Special valve for floor applications ensures sharp edges
- Specially for use in Speedliner<sup>2</sup>
- Containers: 500 ml
- For permanent markings
- Highly resistant to abrasion

### Physical and chemical data

- **Colours:** transparency
- **Storage stability:**  
10 years if appropriate storage provided (=10°-25°C, relative air humidity max. 60%).
- **Efficiency:**  
Depending on condition and colour of the ground,  
500 ml are sufficient for approx. 50 m of 10 cm wide lines  
**Drying (at 20°C, 50% relative air humidity):**  
Dust-dry: after approx. 10 minutes  
Dry to touch: after approx. 30 minutes  
Cured: after approx. 24 hours  
Can be overworked: after approx. 24 hours  
The drying time depends of temperature of surroundings, air humidity and thickness of the applied layer.
- **Contents:** aerosol cans with max. nominal volume of 500 ml

### Environment and labelling

**Environmentally compatible:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

*Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.*

**Labelling:** All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

### Using Instructions

**Before use, carefully read and observe the warning texts on the label!**

- Shake can for approx. 3 minutes.
- After you hear the sound of the balls inside the can, vigorously shake the can for one more minute.
- Test spray at an invisible spot.
- Spray distance approx. 25 cm.
- Apply the desired marking.
- In case of use in the Speedliner<sup>2</sup> marking trolley, attend to the corresponding manual.
- Mineral substrates must have set well, new concrete must be at least 4 - 6 weeks old
- The substrate must be dry, clean, free of fat and stable, loose and sanding layers are to remove
- Concrete and screed must still have sufficient absorptive capacity to ensure adhesion

### Tips for spray painting

Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

### Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of October 6, 2022

This release replaces all eventually earlier issued versions.

Print date: 01.05.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)