

Technical Information Sheet Wheel Spray



ColorMatic wheel spray is a high-quality acrylic paint with high coverage and faster drying time. Professional broad-jet atomization provides an excellent flow and guarantees positive results.

For optimum adhesion, the aluminium wheels should be primed with ColorMatic 1K Grundierung for aluminium no. 180278. Steel wheels should be primed with ColorMatic 1K Primer Filler no. 180278.

Application:

Ideal for coating new or used car rims.

Quality and properties

- Simple time-saving application
- Fast drying time
- Exceptionally high coverage
- Resistant to stone chips, road salt, etc.
- Abrasion resistant
- Robust against damage during automatic car wash

Physikalische und chemische Daten

- **Basis of binder:** NC
- **Colour:** black (no. 190353), silver satin glossy (no. 190377)
- **Smell:** solvent
- **Degree of gloss:** (at measurement angle 60° acc. to DIN 67530) glossy: 80 gloss units
- **Efficiency:** Depending on consistence and colour of the ground: 400 ml are sufficient for approx. 0,8 - 1,0 m²
- **Substrate:** Thoroughly cleaned, new or second-hand steel or aluminium wheel rim
- **Drying time (at 20°C, 50% relative air humidity):** Dust-dry: after approx. 10 minutes
Dry to touch: after approx. 30 minutes
The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.
- **Temperature resistance:** to 60°C
- **Storage stability:** 10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:** Aerosol cans, maximum nominal volume 400 ml
- **VOC-value:** 273,1g

Environment and labelling

Environmentally compatible: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,




Using instructions

Before use, carefully read and observe the warning texts on the label!

- Clean the surfaces to be painted thoroughly with ColorMatic silicone cleaner no. 174469, then sand
- The area must be dry and free of dust and grease
- Shake can vigorously for 2 minutes
- Carry out spray test
- For optimum adhesion before application, the aluminium wheels can be primed with ColorMatic 1K primer for aluminium no. 180 278 - steel wheels with ColorMatic 1K primer filler
- 2-3 coats
- **For professional use only**
- **Wear an appropriate respirator (recommended type A2/P3)**

Hints concerning application

Also suitable for coating exhaust tail-pipes.



2 min

2-3

5 min

20°C=60 min

Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of July 26, 2010

This release replaces all eventually earlier issued versions

Print date: 30.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com