

## Technical Information Plastic Primer



DUPLI-COLOR PLASTIC PRIMER is the perfect bonding agent for the final varnishing of car plastic parts. Suitable for garden furniture and other objects of coatable hard plastics.

Applicable for following hard plastics:  
 polyurethane (PUR)  
 polystyrene (PS)  
 polyamide (PA)  
 polypropylene rubber, modified (EPDM),  
 acrylic butadiene styrene plastics (ABS)  
 glass-fibre reinforced plastics (GfK)  
 hard polyvinyl chloride (Hart-PVC)

After priming with PLASTIC PRIMER you can paint the objects with any DUPLI-COLOR synthetic, nitro-combi or acrylic spray paint.

### Quality and properties

- Solvent-based product with special adhesion-promoting additives
- Quick-drying
- Suitable for indoors and outdoors applications
- Good resistance to outside influences
- Good flow, smooth surface

### Physical and chemical data

- **Basis of the binder:** special resin
- **Colour:** transparent
- **Smell:** solvent
- **Degree of gloss:** at measurement angle 60° acc. to DIN 67530 not applicable
- **Efficiency:**  
 150 ml are sufficient for approx. 1.8 - 2.3 m²  
 400 ml are sufficient for approx. 5 - 6 m²
- **Drying time (at 20°C, 50% relative air humidity)::**  
 Dry and coatable: after approx. 15 minutes  
 The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.
- **Temperature resistance:** not applicable
- **Storage stability:**  
 10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**  
 aerosol cans, maximum nominal volume 150 ml resp. 400 ml

### Environment and labelling

**Environmentally compatible:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

*Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.*

**Labelling:** All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

### Using instructions

The most DUPLI-COLOR spray paints have a so-called no-spray ring or a tamper-proof cap. This is to avoid unauthorized use. Please see the corresponding advises on the cap or on the label.

**Before use, carefully read and observe the warning texts on the label!**

### Applications

#### Preparation of the ground:

- Clean surface from dirt, fat and silicone.
- Evtl. sand with sandpaper grain 600.
- Remove abrasive dust.

#### Lacquering:

- Before use, shake can for 3 minutes.
- Test spray at an invisible spot.
- Apply max. 2 thin layers.
- Spray from a distance of approx. 25 cm.
- After drying (approx. 15 minutes) coatable with acrylic, synthetic or nitro-combi lacquers.

### Tips for spray painting

Protect the object and the surrounding area from spray mist. When painting small areas it is recommended that a piece of card is used as a mask, with a hole cut in it slightly larger than the area to be sprayed. The mask should be held 1 to 2 cm from the surface. With this method, the mainly part of the spray mist is brought under control. It recommends to mask parts not to be lacquered, to protect the surrounding against the spray mist.

The aerosol can should have room temperature.

Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

#### **Disclaimer of liability**

---

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of August 20, 2012

This release replaces all eventually earlier issued versions.

Print date: 28.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)