

## Technical Information Universal Primer



DUPLI-COLOR Universal Primer for the optimal adhesion of subsequent coatings. It is ideal as a primer for new coatings and renovation inside and outside, such as furniture, doors, windows etc.

Possible surfaces are wood, metal (iron, zinc), paintable plastics, plastering, concrete, masonry.

### Quality and properties

- ease of handling
- good filling behavior
- good sandable
- for inside and outside use

### Physical and chemical data

- **Basis of the binder:** alcyde resin
- **Colour:** grey
- **Smell:** solvents
- **Degree of gloss** (at measurement angle 60° acc. to DIN 67530): not relevant
- **Efficiency:**  
per 250 ml can: 2.5 - 3 m<sup>2</sup>  
per 750 ml can: 7.5 - 9 m<sup>2</sup>
- **Drying time (at 20°C, 65% relative air humidity):**  
Surface-dry after approx. 4-6 hours  
Coatable after 24-36 hours  
The drying time depends on surrounding temperature, air humidity and absorptivity of the ground.
- **Best working temperature and object temperature:**  
Object temperature min. +7°C
- **Cleaning of tools:** immediately after use with a brush cleaner
- **Storage stability:**  
5 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%) in the unopened original container.  
Do not store below 5°C
- **Size:** metal tins 250 ml and 750 ml

### Environment and labelling

**Environmentally compatible:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

*Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.*

**Labelling:** All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

### Using instructions

**Before use, carefully read and observe the warning texts on the label!**

#### Preparation of the ground:

- The surface has to be bearing, dry, clean and free from fat and rust.
- Remove old flaking paintings which are not bearing.
- Clean zinc-coated surfaces with zinc cleaner or a household cleaner (with addition of liquid ammonia)
- Sand down and clean good maintained coatings, then test compatibility of the coating with a sample coating.

#### Painting:

- Before application, always carefully stir up the paint.
- Temperature of the object and surrounding temperature should be at least +7°C.
- Brush, roll or spray (adjust to spray viscosity).
- Prime coat with this universal primer, final coat with a undiluted, synthetic based lacquer.
- Always before you apply a coat, slightly sand and clean the ground.
- Directly after use clean the tools with a brush cleaner.

### Order information

### Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not

exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of April 11, 2018

This release replaces all eventually earlier issued versions.

Print date: 27.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)