

Technical Information Wood Lasure 2in1 Brush Paint



DUPLI-COLOR Wood Lasure and Primer 2in1 is a solvent-containing, thin film glaze for wood. Exemplary uses are fences, garden houses, carports, doors etc. The glaze is a decorative, long-lasting weather protection, which accentuates the natural wood grain. Only suitable for outside.

Quality and properties

- solvent-based
- free from aromatic compounds
- water-repellent
- UV-resistant
- for outside
- weather-resistant
- breathable

Physical and chemical data

- **Basis of the binder:** Alcyd resin
- **Colour:** misc.
- **Smell:** solvent
- **Degree of gloss** (at measurement angle 60° acc. to DIN 67530): not relevant
- **Efficiency:**
750 ml are sufficient for approx. 9 m²
5 L are sufficient for approx. 60 m²
- **Drying time (at 20°C, 65% relative air humidity):**
Coatable after 24 hours
The drying time depends on surrounding temperature, air humidity and absorptivity of the wooden ground.
- **Storage stability**
5 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%) in the unopened original container.
Do not store below 5°C
- **Size:** metal tins 750 ml and 5 L

Environment and labelling

Environmentally compatible: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using instructions

Before use, carefully read and observe the warning texts on the label!

Preparation of the ground:

- The surface has to be dry, clean and free from fat and rust.
- Sand wheathered wood parts, sand old glaze paintings.

Painting:

- Before application, always carefully stir up the paint.
- Apply non-diluted with a brush.
- Apply 1-2 coats depending on demand.
- Brush in the direction of the fiber.

Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of March 14, 2018

This release replaces all eventually earlier issued versions.

Print date: 27.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com

