

Technical Information Repair Tape HPX 6200

Very strong, universal high quality tape with stengthened backing and high adhesive strength. Suitable for securing and repairing pipes, tubes, garden hoses, etc.



Quality and properties

Physikalische und chemische Daten

- Various colours, widths and lengths available
- Easy to tear off
- On most subsurfaces removable without leaving residues •
- Waterproof
- · For indoor and outdoor use

- Adhesive: natural rubber
- Carrier: woven cloth/polyester with polyethylene coating
- Maximum temperature: 60°C (temporary till 80°C) Tensile strength: 183 N/ 25 mm
- •
- Adhesive strength: 13 N/ 25 mm
- . Thickness: 0,30 mm

Using instructions

Temperature: Between 0°C and +30°C

Surface must be clean and free from dust and grease. Stored under appropriate conditions shelf life will be a minimum of 36 months.

Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of August 14, 2014 This release replaces all eventually earlier issued versions.

Print date: 06.05.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com