

Technical Information Exhaust Assembly Paste



presto Exhaust Assembly Paste is a putty-like paste to seal joints in the field of exhaust systems, such as sleeves, terminals, clamps etc.

For the repair of wholes, cracks etc. in exhaust system we recommend presto Exhaust Repair Paste.

Quality and properties

- Putty-like paste basing on water glass
- For durable sealing of exhaust system parts
- Quick and easy application
- Ease of disassembling

Physical and chemical data

- **Basis:** Water glass
- **Consistency:** pasty
- **Colour:** dark-grey
- **Smell:** nearly without odour
- **Temperature resistance:** up to approx. 700°C
- **Processing temperature:** +5°C - +30°C, best results during room temperature
- **ph-value:** 9.8
- **Density at 20°C:** 1.68 kg/dm³ ± 0.02 kg/dm³
- **Solid content:** 71 ± 1 %
- **Storage stability:** 12 months if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:** 60 g and 170 g tube

Environment and labelling

Environmentally compatible: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using instructions

Before use, carefully read and observe the warning texts on the label!

Application:

- The substrate has to be clean and fat free.
- The paste can be applied generously onto the spots to be treated, then the parts can be assembled immediately.
- Hardening will happen after starting the vehicle in the usual way by means of heating.

Order informations

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of August 24, 2010

This release replaces all eventually earlier issued versions.

Print date: 29.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com