

Technisches Merkblatt Kunstharz-Verdünner



presto Resin thinner is a diluent for commercial air- and oven-drying synthetic resin paints, baking enamels, silver bronzes, zinc dust paints etc. The slow evaporation of the dilution guaranteed to delay a good course of painting without the drying oxidatively drying paints. Please consider the instruction of the varnish manufacturer. In case of doubt please make a pretest.

Qualität und Eigenschaften

- Universal diluent for all solvent-borne synthetic resin and chlorinated rubber paints
- Suitable as a cleaning agent and degreaser of metals
- For removing paint splashes and paint stains

Physikalische und chemische Daten

- **Color:** colourless
- **Smell:** characteristic
- **Boiling point:** 130 °C
- **Flash point:** > 25 °C
- **Density:** 0,79 g/cm³

Environment and labelling

Environmentally compatible: European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using instructions

Before use, carefully read and observe the warning texts on the label!

Anwendung

- Sparsam verwenden.
- Gut in die zu verdünnende Farbe einführen.
- Hinweise des Lackherstellers beachten.
- Im Zweifelsfall bitte Vorversuch durchführen.

Bestellangaben

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of: 07.02.2011

This release replaces all eventually earlier issued versions.

Print date: 05.05.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com