

Technical Information Aluminium Filler



presto Aluminium Putty is a 2-component polyester filling putty as mixture of a medium-elastic, highly reactive, amino-preaccelerated polyester resin with different mineral, environment-friendly fillers and aluminium pigments.

Applicable as filling compound for car repair, engine construction and for hobby works. Everywhere, where a large-area spreading is desired. Surfaces like metal, wood, div. plastics and concrete are easy to fill in the desired layer thickness. To fill and level out holes and to stabilise flimsy spots.

For preparation and finishing your filling job, we recommend our presto sand papers. We offer a wide assortment of fine and coarse papers for dry and wet sanding.

Order informations

Color	Product	Bundle	Art.No.
	presto Alu-Spachtel AY 250g	250 g	318481
	presto Alu-Spachtel AY 250g	250 g	483022
	presto Aluspachtel AY 1000g	1 KG	318504
	presto Aluspachtel AY 1000g	1 KG	483046
	presto Aluspachtel AY 500g	500 g	481307

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of February 24, 2011

This release replaces all eventually earlier issued versions.

Print date: 29.04.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com