

## Technical Information Contact Spray



presto contact spray is the reliable way to avoid contact resistance, leakage current and voltage losses in electrical connections. It also ensures a smooth current.

Application areas:  
electrical connections, radios, televisions, tools, cabling, connections

### Quality and properties

- Water and moisture are infiltrated and displaced
- Excellent adhesion and penetration
- Protects contacts and prevents corrosion
- Resistant to water, salts and weak bases
- Directed jet spray
- This product is equipped with a special cap, which contains a tube and a spray nozzle that can be used to reach inaccessible places.
- Observe TRG 300

### Physical and chemical data

- **Colour:** yellow/transparent
- **Propellant:** propane/butane
- **Density at 20°C:** 0,664 g/ml
- **Vapour pressure at 20°C:** 4 - 4,5 bar
- **Storage stability:**  
10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Size:**  
aerosol can, maximum nominal volume 400 ml

### Environment and labelling

**Environmentally compatible:** European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal:** Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

*Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.*

**Labelling:** All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

### Using instructions

**Before use, carefully read and observe the warning texts on the label!**

#### Application:

- Make sure can is at room temperature.
- Application temperature 5 ° to 30 ° C.
- Switch electrical equipment off before treating.
- Surfaces must be clean, dry and free of grease.
- Shake can well before use.
- Spray several thin layers on connectors, cables, distributor caps, etc.

### Order informations

### Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of March 12, 2014

This release replaces all eventually earlier issued versions.

Print date: 05.05.2024

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)