

Technical Data Sheet Spotmarker fluo/non-fluo



Professional construction site marking for building construction and civil engineering, construction sites and road construction. Also can be used in tunnelling and mining.

Practical lockable twist cap for a clean, precise and at the same time rich spray pattern.

Colour tones: luminous pink, luminous red, luminous orange, luminous yellow, luminous green and luminous blue for fluorescent markings.

Also available in non-fluorescent colour hues: white, yellow, red and black.

The black marking spray can also be used as corrective sprays to remove fluorescent markings from tar.

Fluo/non-fluo Spotmarker can also be used in the following [accessories](#):

- Marking pistol
- Marking wand

Accessories available from all COLORMARK partners.

Quality and properties Physical and chemical data

- Practical lockable twist cap
- Special tilt valve for accurate wall and floor markings
- Outstanding adhesion also to wet surfaces
- Markings remain strongly visible for 12 months
- High coverage quality ensures high yield of up to 250 m
- Reliable spraying down to -20°C
- Intensive luminosity of the fluorescent hues
- Also easy to apply with gloves
- Clean, drip-free marking
- For the best possible recyclability, the cap can be easily separated from the can after emptying
- Can be reliably sprayed until empty
- **Colours:** fluorescent: pink, red, orange, yellow, green, blue; non-fluo: white, yellow, red, black
- **Storage stability:**
Aerosols: 10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Efficiency:**
Depending on consistence and color of the ground 500 ml are sufficient for approximately 200-250 m
- **Drying time (at 20°C, 50% relative air humidity):**
Dust-dry: after approx. 10 minutes
Dry to touch: after approx. 30 minutes
Cured: after approx. 24 hours
Coatable: after approx. 24 hours
The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.
- **Size:** aerosol cans, maximum nominal volume 500 ml

Disposal and labelling

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using Instructions

Before use, carefully read and observe the warning texts on the label!

- Shake can for approx. 3 minutes.
- Test spray at an invisible spot.
- Spray distance approx. 5-15 cm.
- Apply the desired marking.
- Only conditionally applicable on mineral substrates.

Tips for spray painting

<link typo3 sysext cms layout bearbeiten>Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of November 13, 2025

This release replaces all eventually earlier issued versions.

Print date: 26.08.2026

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com