Technical Data Sheet Chalkmarker

The COLORMARK Chalkmarker is ideal for markings that should remain visible only for a short time (e.g. for sporting events, fairs, identification of accident sites). Thanks to the special chalk base, the marking holds for just a few days to weeks and fades quickly during extended periods of rain or in high-traffic areas. Ideally suited for garden and landscaping as well as for sports and golf courses.

Practical lockable twist cap for a clean, precise and at the same time rich spray pattern.

Colour hues: white, yellow, red, blue, green, orange, pink

Also available as 750 ml can for use in Speedliner² in white

The Eventmarker can be used in the following accessories:

- Marking pistol (only for 500 ml can)
- Marking wand (only for 500 ml can)
- Speedliner² (only for 750 ml can)
- Speedmarker long (only for 750 ml can)
- Speedmarker short (only for 750 ml can)
- Speedmarker 2-Wheel (only for 750 ml can)

Accessory available from all COLORMARK partners.

Quality and properties

- For temporary markings
- No damage to the marked object
- For indoor and outdoor applications
- Easily removed with water
- Praktische, verschließbare Drehkappe für ein sauberes, präzises und gleichzeitig reichhaltiges Sprühmuster
- Special tilt valve for accurate wall and floor markings
- Outstanding adhesion to wet surfaces as well
- High coverage quality ensures high yield
- Depending on the nature and color of the substrate, 500 ml can cover up to 260 m and 750 ml up to 390 m
- Reliable spraying down to -20°C
- Simple to use also with gloves
- Clean, drip-free marking
- Cap acceptable for special applications (for use in accessories)
- For the best possible recyclability, the cap can be easily separated from the can after emptying

Physical and chemical data

- **Colours:** white, yellow, red, blue, green, orange, pink
- **Storage stability:**
  Aerosols: 10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)
- **Efficiency:**
  Depending on consistence and color of the ground
  500 ml are sufficient for up to 260 m
  750 ml are sufficeint for up to 390 m
- **Drying time (at 20°C, 50% relative air humidity):**
  Dust-dry: after approx. 10 minutes
- **Size:** aerosol cans, maximum nominal volume 500 resp. 750 ml

Disposal and labelling

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".
Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance

with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using Instructions

Before use, carefully read and observe the warning texts on the label!

- Shake can for approx. 3 minutes.
- Test spray at an invisible spot.
- Spray distance approx. 5-15 cm.
- Apply the desired marking.
- In case of use in the Speedliner² marking trolley, attend to the corresponding <link fileadmin images content produkte colormark aufbauanleitung-speedliner.pdf _blank download>manual.

Tips for spray painting

<link typo3 sysext cms layout bearbeiten>Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of November 13th, 2025
This release replaces all eventually earlier issued versions.

Print date: 16.10.2026

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com