Technical Data Sheet Floor Marking Brush Paint



Fast-drying marking paint with good coverage and excellent processing properties. For interior and exterior use. Lacquer-like, easy-to-clean surface. Well suited for new and maintenance markings on roads and car parks with light to medium traffic load. All substrates have to be sound, dry and free from dust,oil and grease. Roughen smooth substrates, prime highly absorbent ones.

Processing:

- paint
- rolling
- airless spraying

Quality and properties

- Fast drying
- High hiding power
- Dirt repellent
- For interior and exterior use
- Excellent processing properties
- For new and maintenance marking
- Lacquer-like, easy-to-clean surface
- High resistance to light and weather

Physical and chemical data

- **Colours:** white, yellow
- **Storage stability:**
  24 month if appropriate storage provided (=10°-25°C, relative air humidity max. 60%).
- **Efficiency:**
  Depending on condition and colour of the ground,
  750 ml are sufficient for approx. 2,5 - 4 m²
- **Drying (at 20°C, 55% relative air humidity):**
  Dust dry: after approx. 30 min
  Dry to touch: after approx. 10-15 min
- **Contents:** paint cans with max. nominal volume of 750 ml
-
  - **Minimum Working Temperature:** 8 °C
  - **Maximum Working Temperature:** 30 °C
  - **Vapour pressure:** 247/20 bar
  - **Flash point:** <-18 °C

Disposal and labelling

Disposal: Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".
Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.

Labelling: All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH 1907/2006/EG, article 31 und appendix II,

Using Instructions

Before use, carefully read and observe the warning texts on the label!

Application:
For professional use only

Application:
By brushing, spraying or rolling. The processing should be easy and quick, because the paint quickly absorbs. On asphalt and similar surfaces, especially in summer, spraying is preferable to painting. During the entire processing and drying time, the material, substrate and air temperatures must not fall below 8°C and must not exceed 30°C. The air humidity should not be between 30% r.H. and 75% r.H during the entire time.

Tips for spray painting

<link typo3 sysext cms layout bearbeiten>Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of October 28, 2022

This release replaces all eventually earlier issued versions.

Print date: 06.11.2026

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com