



Technical Information Side moulding tape



Double sided foam tape with high adhesive strength. Suitable for mounting all kinds of objects such as trims, signs etc.

Quality and Properties Physical and chemical data

- High adhesive strength
- Good adhesion to clear coating, metal, glass and most plastics
- Weather resistant, suitable for long term outdoor use
- With MSE technology
- Solvent resistant

- **Adhesive:** acrylic
- **Carrier:** polyethylene foam
- **Maximum temperature:** 100°C
- **Adhesive strength:** 29 N/ 25 mm
- **Shear strength:** 6,6 kg/ cm²
- **Thickness:** 1,05 mm

Using instructions

Temperature: Between 0°C and +30°C.

Surface must be clean and free from dust and grease. Stored under appropriate conditions shelf life will be a minimum of 36 months.

Order information

Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of June 26, 2014

This release replaces all eventually earlier issued versions.

Print date: 15.08.2026

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | info-de@european-aerosols.com