



## Technical Information Fly Clear Lacquer



Fly Clear Lacquer is a high-grade clear varnish for spray paints on acrylic or nitro-combi basis, such as Metallic-, Neon- and other paint sprays,

## Quality and properties      Physical and chemical data

- High-grade acrylic quality
- Excellent adhesion
- Good flow, smooth surface
- Quick-drying
- Suitable for painting objects for indoor and outdoor uses
- Weather-resistant, light-proof, UV-resistant
- After drying scratch-, shock- and impact-resistant

- **Basis of the binder:** Acrylate copolymeres
- **Colour:** transparent
- **Smell:** solvent
- **Degree of gloss** (at measurement angle 60° acc. to DIN 67530):  
glossy: 80 - 90 gloss units  
matt: 15- 20 gloss units
- **Efficiency:**  
Depending on consistence and color of the ground:  
400 ml are sufficient for 1-1,5 m<sup>2</sup>
- **Drying time (at 20°C, 50% relative air humidity):**  
Dust-dry: after approx. 15 minutes  
Dry to touch: after approx. 30 minutes  
Cured, can be polished: after approx. 24 hours  
The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.
- **Temperature-resistant:** up to 80°C
- **Storage stability:**  
10 years if appropriate storage provided  
(=10°-25°C, relative air humidity of max. 60%)
- **Size:** aerosol cans, maximum nominal volume 400 ml

## Disposal and labelling

**Disposal:** Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as "special refuse".

*Only for DE: In order to ensure a high reuse and recycling rate, the legislator requires, in accordance with §15 - VerpackG, Paragraph 1, the return of transport, sales or outer packaging, alternatively, however, deviating agreements can also be made.*

**Labelling:** All products of European Aerosols comply with the current status of their labelling regulations. Classification and distinction takes place by the presently legal form of the **Globally Harmonized System of Classification and Labelling of Chemicals** (GHS) or rather by CLP 1272/2008/EG regulations. Our safety data sheets comply with the current form of REACH

## Using instructions

The most DUPLI-COLOR spray paints have a so-called no-spray ring or a tamper-proof cap. This is to avoid unauthorized use. Please see the corresponding advises on the cap or on the label.

**Before use, carefully read and observe the warning texts on the label!**

### Application

- Remove rust and dirt.
- If necessary sand the surface, in order to improve the adhesion.
- The ground has to be clean, dry and free from fat.
- Cover areas not to be painted.
- Before use, shake can for 3 minutes.
- Test spray at an invisible spot.
- Spray from a distance of 25 - 30 cm several thin cross-coats of the clear lacquer.
- Do not spray over surfaces which are painted with synthetic resin lacquer!

## Tips for spray painting

Protect the object and the surrounding area from spray mist. When painting small areas it is recommended that a piece of card is used as a mask, with a hole cut in it slightly larger than the area to be sprayed. The mask should be held 1 to 2 cm from the surface. With this method, the mainly part of the spray mist is brought under control. It recommends to mask parts not to be lacquered, to protect the surrounding against the spray mist.

The aerosol can should have room temperature.

Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

## Order information

## Disclaimer of liability

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. European Aerosols is let off the liability, unless the liability-based incident is caused by a fault incurred to European Aerosols.

As of June 15, 2016

This release replaces all eventually earlier issued versions.

Print date: 15.08.2026

European Aerosols GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)