

Page 1/10

\*

\*

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.06.2022

Version number 114 (replaces version 113)

Revision: 30.03.2022

	dentification of the substance/mixture and of the company/undertaking
1.1 Product identifi	fier
Trade name: MOT	TIP ZINC SPRAY 400 ML
No further relevant Sector of Use SU21 Consumer u SU22 Professional Product category P Process category PROC7 Industrial PROC11 Non indu	tified uses of the substance or mixture and uses advised against at information available. uses: Private households / general public / consumers al uses: Public domain (administration, education, entertainment, services, craftsmen) Paint remover
Manufacturer/Supp European Aerosols Wolfraamweg 2 NL-8471 XC Wolve The Netherlands Tel : +31 (0)561 69 e-mail: sds-nl@euro *Formerly known a Further informatio 1.4 Emergency tele	s B.V.* Pega 194400 uropean-aerosols.com as Motip Dupli B.V. <b>ion obtainable from:</b> Department Product Safety
UK: NPIS National	al Poisons Information Centre Tel: +44 0344 892 0111
SECTION 2: He	Iazards identification
	of the substance or mixture ording to Regulation (EC) No 1272/2008
	oraing to Regulation (EC) NO 1272/2008
flame	
	H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated
Aerosol 1	
Aerosol 1	ment
Aerosol 1 Aerosol 1 environm Aquatic Acute 1	ment H400 Very toxic to aquatic life.
Aerosol 1	ment H400 Very toxic to aquatic life.
Aerosol 1 Aerosol 1 Aquatic Acute 1 Aquatic Chronic 1	ment H400 Very toxic to aquatic life.


# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.06.2022

Version number 114 (replaces version 113)

Revision: 30.03.2022

#### Trade name: MOTIP ZINC SPRAY 400 ML



## **SECTION 3: Composition/information on ingredients**

· Dangerous components:	1. 1. 1. 1	25 . 500/
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37	dimethyl ether Flam. Gas 1A, H220 Press. Gas (Comp.), H280	25-<50%
CAS: 7440-66-6 EINECS: 231-175-3 Index number: 030-001-01-9 Reg.nr.: 01-2119467174-37	zinc powder -zinc dust (stabilized) � Aquatic Acute 1, H400; Aquatic Chronic 1, H410	25-<50%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	5-<10%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335-H336 EUH066	5-<10%
		(Contd. on page 3

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.06.2022

Version number 114 (replaces version 113)

Revision: 30.03.2022

# Trade name: MOTIP ZINC SPRAY 400 ML

		Contd. of page 2)
EC number: 905-588-0	xylene	5-<10%
Reg.nr.: 01-2119488216-32-xxxx	<ul> <li>Flam. Liq. 3, H226</li> <li>STOT RE 2, H373; Asp. Tox. 1, H304</li> <li>Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335</li> </ul>	-
CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 Reg.nr.: 01-2119463881-32	zinc oxide	_ <2.5%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

# **SECTION 4:** First aid measures

· 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- $\cdot$  4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** *No further relevant information available.*

# **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- $\cdot$  5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

# SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.
- Keep away from ignition sources.
- · 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
   See Section 7 for information on safe handling.
   See Section 8 for information on personal protection equipment.
   See Section 13 for disposal information.

# **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

ЗB

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.06.2022

Version number 114 (replaces version 113)

Revision: 30.03.2022

(Contd. of page 3)

### Trade name: MOTIP ZINC SPRAY 400 ML

No sn	ocial	measures	romirod	

- Information about fire and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Keep respiratory protective device available.
- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurised containers.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

· Storage class: 2 B

• 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

#### 115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m<sup>3</sup>, 500 ppm Long-term value: 766 mg/m<sup>3</sup>, 400 ppm

### 67-64-1 acetone

WEL Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppm Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

#### xylene

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm Long-term value: 220 mg/m<sup>3</sup>, 50 ppm Sk; BMGV

#### · Ingredients with biological limit values:

#### xylene

BMGV 650 mmol/mol creatinine Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Avoid contact with the eyes.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

(Contd. on page 5)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.06.2022

Version number 114 (replaces version 113)

Revision: 30.03.2022

(Contd. of page 4)

### Trade name: MOTIP ZINC SPRAY 400 ML

· Hand protection



Protective gloves

#### • *Material of gloves Butyl rubber, BR*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

# · Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to: Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· Eye/face protection



\*

Tightly sealed goggles

# SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical p	roperties
· General Information	-
· Physical state	Aerosol
· Colour:	Grey
· Odour:	Solvent-like
· Odour threshold:	Not determined.
• Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling	
range	Not applicable, as aerosol.
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	3.3 Vol % (115-10-6 dimethyl ether)
· Upper:	26.2 Vol %(115-10-6 dimethyl ether)
· Flash point:	Not applicable, as aerosol.
· Ignition temperature:	>400 °C ( $>752$ °F) (Hydrocarbons, C9, aromatics)
• Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C (68 °F):	4000 hPa (3000.2 mm Hg)
· Density and/or relative density	
• Density at 20 •C (68 •F):	1.1 g/cm <sup>3</sup> (9.2 lbs/gal)
· Relative density	Not determined.
	(Contri on no

(Contd. on page 6)

GB

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.06.2022

Version number 114 (replaces version 113)

Revision: 30.03.2022

## Trade name: MOTIP ZINC SPRAY 400 ML

	(Contd. of page
· Vapour density	Not determined.
9.2 Other information	
· Appearance:	
· Form:	Aerosol
<ul> <li>Important information on protection of heat environment, and on safety.</li> </ul>	lth and
• Explosive properties:	Not determined.
· Solvent content:	
· Organic solvents:	59.2 %
$\cdot VOC(EC)$	
	648.3 g/l
· VOC-EU%	59.21 %
· Solids content:	40.7 %
· Change in condition	
· Evaporation rate	Not applicable.
· Information with regard to physical hazard	classes
· Explosives	Void
· Flammable gases	Void
·Aerosols	Extremely flammable aerosol. Pressurised container:
	May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
• Substances and mixtures, which emit flamn	
gases in contact with water	Void
• Oxidising liquids	Void
• Oxidising solids	Void
• Organic peroxides	Void
· Corrosive to metals	Void
• Desensitised explosives	Void

## SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

\*

2

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

#### **SECTION 11: Toxicological information**

#### · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity

· LD/LC50 values relevant for classification:

7440-66-6 zinc powder -zinc dust (stabilized)

>2000 mg/kg (rat) (OECD 401) Oral LD50

(Contd. on page 7)

GB

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.06.2022

Version number 114 (replaces version 113)

Revision: 30.03.2022

# Trade name: MOTIP ZINC SPRAY 400 ML

		(Contd. of page 6)
Inhalative	LC50 / 4 h	>5410 mg/m3 (rat) (OECD 403)
67-64-1 ac	etone	
Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	>15800 mg/kg (rabbit)
Inhalative	LC50 / 4h	76 mg/l (rat)
xylene		
Oral	LD50	3523 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	29000 mg/m3 (rat)
• Serious ey • Respirator	e damage/ir y or skin sei	on No irritant effect. ritation Causes serious eye irritation. nsitisation No sensitising effects known. ther hazards
·Endocrine		

None of the ingredients is listed.

# **SECTION 12: Ecological information**

## · 12.1 Toxicity

×

# • Aquatic toxicity:

# 115-10-6 dimethyl ether

EC50/96 h 155 mg/l (algae) LC50/48 h >4000 mg/l (daphnia magna)

LC50 / 96 h >4000 mg/l (fish)

# 67-64-1 acetone

LC50/96h 8300 mg/l (fish)

EC50/96h 7200 mg/l (algae)

LC50 / 48 h 8450 mg/l (crustacean (water flea))

# xylene

EC50 / 48 h 7.4 mg/l (daphnia magna)

LC50/96 h 13.5 mg/l (fish)

· 12.2 Persistence and degradability No further relevant information available.

- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- · Remark: Very toxic for fish
- · Additional ecological information:

· General notes:

- Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
- Do not allow product to reach ground water, water course or sewage system.
- Danger to drinking water if even small quantities leak into the ground.
- Also poisonous for fish and plankton in water bodies.
- Very toxic for aquatic organisms

(Contd. on page 8)

GR

Page 8/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.06.2022

Version number 114 (replaces version 113)

Revision: 30.03.2022

## Trade name: MOTIP ZINC SPRAY 400 ML

(Contd. of page 7)

# **SECTION 13: Disposal considerations**

### · 13.1 Waste treatment methods


· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

#### · Uncleaned packaging:

# · Recommendation:

Disposal must be made according to official regulations. Disposal must be made according to official regulations.



Page 9/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.06.2022

Version number 114 (replaces version 113)

Revision: 30.03.2022

# Trade name: MOTIP ZINC SPRAY 400 ML

	(Contd. of page
EMS Number:	F- $D$ , $S$ - $U$
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1
	litre: Category A. For AEROSOLS with a capacity
	above 1 litre: Category B. For WASTE AEROSOLS:
	Category C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1
	litre:
	Segregation as for class 9. Stow "separated from" clas 1 except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class
	2.
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class
	2.
14.7 Maritime transport in bulk according	z to IMO
instruments	Not applicable.
Transport/Additional information:	
ADR	
· Limited quantities (LQ)	1L
$\cdot$ Excepted quantities ( $\widetilde{EQ}$ )	Code: E0
· · · · · ·	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
· IMDG	
Limited quantities (LQ)	1L
• Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity
UN ''Model Regulation'':	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY
5	HAZARDOUS

# **SECTION 15: Regulatory information**

 $\cdot$  15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

\*

- *E1 Hazardous to the Aquatic Environment P3a FLAMMABLE AEROSOLS*
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · National regulations:
- Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57
- None of the ingredients is listed.

(Contd. on page 10)

GB

Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.06.2022

Version number 114 (replaces version 113)

Revision: 30.03.2022

#### Trade name: MOTIP ZINC SPRAY 400 ML

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. of page 9)

GB

# **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- *H410 Very toxic to aquatic life with long lasting effects.*
- H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing SDS: R&D legislation and regulatory advisor

#### · Contact: e-mail: sds-nl@european-aerosols.com

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the
- International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- SVHC: Substances of Very High Concern
- vPvB: very Persistent and very Bioaccumulative
- Flam. Gas 1A: Flammable gases Category 1A
- Aerosol 1: Aerosols Category 1
- Press. Gas (Comp.): Gases under pressure Compressed gas
- Flam. Liq. 2: Flammable liquids Category 2
- Flam. Liq. 3: Flammable liquids Category 3
- Acute Tox. 4: Acute toxicity Category 4
- Skin Irrit. 2: Skin corrosion/irritation Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard Category 1
- Aquatic Acute 1: Hazardous to the aquatic environment acute aquatic hazard Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment long-term aquatic hazard Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment long-term aquatic hazard Category 2
- \* Data compared to the previous version altered.