

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.09.2022

Version number 5 (replaces version 4)

Revision: 06.09.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

· **Trade name:** DC Tuning Spray Paint Chrome

· **Article number:** 237966

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.

· **Sector of Use**

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Product category** PC9a Coatings and paints, thinners, paint removers

· **Process category**

PROC7 Industrial spraying

PROC11 Non industrial spraying

· **Application of the substance / the mixture** Lacquer

1.3 Details of the supplier of the safety data sheet

· **Manufacturer/Supplier:**

European Aerosols GmbH*

Kurt Vogelsang Strasse 6

D-74855 Haßmersheim

Tel.: +49 (0) 6266 750

e-mail: sds-de@european-aerosols.com

*Formerly known as Motip Dupli GmbH

· **Further information obtainable from:** Department Product Safety

· **1.4 Emergency telephone number:**

Tel.: +49 6266-75-310

Fax +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

UK:

Public emergency phone no: 111

Only for healthcare professionals: 0344 892 0111

Ireland:

Poison center if childs have been poisoned: 01 809 2166 (8:00 am - 10:00 pm, 7 days)

Only for healthcare professionals: 01 809 2566 (24 h / 7 days)

Tox Info Suisse 145 (24-h-emergency number)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

· **Classification according to Regulation (EC) No 1272/2008**



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



health hazard

STOT RE 2 H373

May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 2)

Trade name: DC Tuning Spray Paint Chrome

(Contd. of page 1)



Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
STOT SE 3 H335 May cause respiratory irritation.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

xylene

· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P280 Wear protective gloves / eye protection.

P284 In case of inadequate ventilation wear respiratory protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P312 Call a POISON CENTER/doctor if you feel unwell.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

· **Additional information:**

Buildup of explosive mixtures possible without sufficient ventilation.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

| | | |
|----------------------------|--|---------|
| EC number: 905-588-0 | xylene | 25-<50% |
| Index number: 601-022-00-9 | Flam. Liq. 3, H226 | |
| Reg.nr.: 01-2119488216-32 | STOT RE 2, H373; Asp. Tox. 1, H304 | |
| | Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | |

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.09.2022

Version number 5 (replaces version 4)

Revision: 06.09.2022

Trade name: DC Tuning Spray Paint Chrome

(Contd. of page 2)

| | | |
|--|--|-----------|
| CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21 | propane ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280 | 20-<25% |
| CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32 | butane (containing < 0,1 % butadiene (203-450-8)) ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280 | 12.5-<20% |
| CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27 | isobutane (containing < 0,1 % butadiene (203-450-8)) ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280 | 5-<10% |
| CAS: 7429-90-5 EINECS: 231-072-3 Index number: 013-002-00-1 Reg.nr.: 01-2119529243-45 | aluminium powder (stabilised) ⚠ Flam. Sol. 1, H228; Water-react. 2, H261 | <2.5% |

Additional information:

xylene: Contains ethylbenzene CAS 100-41-4

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures****General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.**After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing agents:**

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

5.3 Advice for firefighters -· **Protective equipment:** Mouth respiratory protective device.**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

· **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.**6.3 Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to item 13.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.09.2022

Version number 5 (replaces version 4)

Revision: 06.09.2022

Trade name: DC Tuning Spray Paint Chrome

(Contd. of page 3)

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

· **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Observe official regulations on storing packagings with pressurised containers.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Keep container tightly sealed.

· **Storage class:** 2 B

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

xylene

| | |
|-----|---|
| WEL | Short-term value: 441 mg/m ³ , 100 ppm |
| | Long-term value: 220 mg/m ³ , 50 ppm |
| | Sk; BMGV |

106-97-8 butane (containing < 0,1 % butadiene (203-450-8))

| | |
|-----|--|
| WEL | Short-term value: 1810 mg/m ³ , 750 ppm |
| | Long-term value: 1450 mg/m ³ , 600 ppm |
| | Carc (if more than 0.1% of buta-1.3-diene) |

7429-90-5 aluminium powder (stabilised)

| | |
|-----|--|
| WEL | Long-term value: 10* 4** mg/m ³ |
| | *inhalable dust ** respirable dust |

· **Ingredients with biological limit values:**

xylene

| | |
|------|---------------------------------|
| BMGV | 650 mmol/mol creatinine |
| | Medium: urine |
| | Sampling time: post shift |
| | Parameter: methyl hippuric acid |

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

(Contd. on page 5)

Trade name: DC Tuning Spray Paint Chrome

(Contd. of page 4)

Avoid contact with the eyes.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

Hand protection

Protective gloves

Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

Eye/face protection

Tightly sealed goggles

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties**General Information****Physical state**

Aerosol

Colour:

According to product specification

Odour:

Characteristic

Odour threshold:

Not determined.

Melting point/freezing point:

Undetermined.

Boiling point or initial boiling point and boiling range

Not applicable, as aerosol.

Flammability

Not applicable.

Lower and upper explosion limit**Lower:**

1 Vol % (xylene)

Upper:

10.9 Vol % (74-98-6 propane)

Flash point:

Not applicable, as aerosol.

Ignition temperature:

365 °C (689 °F) (106-97-8 butane (containing < 0,1 % butadiene (203-450-8)))

Decomposition temperature:

Not determined.

pH

Not determined.

Viscosity:**Kinematic viscosity**

Not determined.

Dynamic:

Not determined.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.09.2022

Version number 5 (replaces version 4)

Revision: 06.09.2022

Trade name: DC Tuning Spray Paint Chrome

(Contd. of page 5)

| | |
|--|--|
| · Solubility | |
| · water: | <i>Not miscible or difficult to mix.</i> |
| · Partition coefficient n-octanol/water (log value) | <i>Not determined.</i> |
| · Vapour pressure at 20 °C (68 °F): | <i>8300 hPa (6225.5 mm Hg) (74-98-6 propane)</i> |
| · Density and/or relative density | |
| · Density at 20 °C (68 °F): | <i>0.7 g/cm³ (5.8 lbs/gal)</i> |
| · Relative density | <i>Not determined.</i> |
| · Vapour density | <i>Not determined.</i> |

| | |
|--|------------------------|
| · 9.2 Other information | |
| · Appearance: | |
| · Form: | <i>Aerosol</i> |
| · Important information on protection of health and environment, and on safety. | |
| · Explosive properties: | <i>Not determined.</i> |
| · Solvent content: | |
| · Organic solvents: | <i>81.1 %</i> |
| · VOC (EC) | <i>---</i> |
| | <i>567.6 g/l</i> |
| · VOC-EU% | <i>81.08 %</i> |
| · Solids content: | <i>18.9 %</i> |
| · Change in condition | |
| · Evaporation rate | <i>Not applicable.</i> |

| | |
|--|---|
| · Information with regard to physical hazard classes | |
| · Explosives | <i>Void</i> |
| · Flammable gases | <i>Void</i> |
| · Aerosols | <i>Extremely flammable aerosol. Pressurised container: May burst if heated.</i> |
| · Oxidising gases | <i>Void</i> |
| · Gases under pressure | <i>Void</i> |
| · Flammable liquids | <i>Void</i> |
| · Flammable solids | <i>Void</i> |
| · Self-reactive substances and mixtures | <i>Void</i> |
| · Pyrophoric liquids | <i>Void</i> |
| · Pyrophoric solids | <i>Void</i> |
| · Self-heating substances and mixtures | <i>Void</i> |
| · Substances and mixtures, which emit flammable gases in contact with water | <i>Void</i> |
| · Oxidising liquids | <i>Void</i> |
| · Oxidising solids | <i>Void</i> |
| · Organic peroxides | <i>Void</i> |
| · Corrosive to metals | <i>Void</i> |
| · Desensitised explosives | <i>Void</i> |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** *No further relevant information available.*
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.*
- **10.3 Possibility of hazardous reactions** *No dangerous reactions known.*
- **10.4 Conditions to avoid** *No further relevant information available.*
- **10.5 Incompatible materials:** *No further relevant information available.*
- **10.6 Hazardous decomposition products:** *No dangerous decomposition products known.*

GB

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.09.2022

Version number 5 (replaces version 4)

Revision: 06.09.2022

Trade name: DC Tuning Spray Paint Chrome

(Contd. of page 6)

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity**

- **LD/LC50 values relevant for classification:**

xylene

| | | |
|------------|------------|-------------------------------|
| Oral | LD50 | 3523 mg/kg (rat) |
| Dermal | LD50 | 2000 mg/kg (rabbit) |
| Inhalative | LC50 / 4 h | 29000 mg/m ³ (rat) |

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

xylene

| | |
|-------------|--------------------------|
| EC50 / 48 h | 7.4 mg/l (daphnia magna) |
| LC50 / 96 h | 13.5 mg/l (fish) |

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:**
Disposal must be made according to official regulations.
Disposal must be made according to official regulations.

GB

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.09.2022

Version number 5 (replaces version 4)

Revision: 06.09.2022

Trade name: DC Tuning Spray Paint Chrome

(Contd. of page 7)

SECTION 14: Transport information

· 14.1 UN number or ID number
· ADR, IMDG, IATA

UN1950

· 14.2 UN proper shipping name
· ADR
· IMDG
· IATA

1950 AEROSOLS
AEROSOLS
AEROSOLS, flammable

· 14.3 Transport hazard class(es)
· ADR



· Class
· Label

2.5F Gases.
2.1

· IMDG, IATA



· Class
· Label

2.1 Gases.
2.1

· 14.4 Packing group
· ADR, IMDG, IATA

not regulated

· 14.5 Environmental hazards:

Not applicable.

· 14.6 Special precautions for user
· Hazard identification number (Kemler code):
· EMS Number:
· Stowage Code

Warning: Gases.
-
F-D,S-U
SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2.
For WASTE AEROSOLS:
Segregation as for the appropriate subdivision of class 2.

· Segregation Code

· 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

· Transport/Additional information:

· ADR
· Limited quantities (LQ)
· Excepted quantities (EQ)

1L
Code: E0
Not permitted as Excepted Quantity

· Transport category
· Tunnel restriction code

2
D

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.09.2022

Version number 5 (replaces version 4)

Revision: 06.09.2022

Trade name: DC Tuning Spray Paint Chrome

(Contd. of page 8)

| | |
|-----------------------------------|--|
| · IMDG | |
| · Limited quantities (LQ) | 1L |
| · Excepted quantities (EQ) | Code: E0 Not permitted as Excepted Quantity |
| · UN "Model Regulation": | UN 1950 AEROSOLS, 2.1 |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a** FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **LIST OF SUBSTANCES SUBJECT TO AUTHORISATION (UK ANNEX XIV)**

- **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

- **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H220 Extremely flammable gas.

H226 Flammable liquid and vapour.

H228 Flammable solid.

H261 In contact with water releases flammable gases.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.09.2022

Version number 5 (replaces version 4)

Revision: 06.09.2022

Trade name: DC Tuning Spray Paint Chrome

(Contd. of page 9)

*Flam. Gas 1A: Flammable gases – Category 1A**Aerosol 1: Aerosols – Category 1**Press. Gas (Comp.): Gases under pressure – Compressed gas**Flam. Liq. 3: Flammable liquids – Category 3**Flam. Sol. 1: Flammable solids – Category 1**Water-react. 2: Substances and mixtures which in contact with water emit flammable gases – Category 2**Acute Tox. 4: Acute toxicity – Category 4**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Irrit. 2: Serious eye damage/eye irritation – Category 2**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2**Asp. Tox. 1: Aspiration hazard – Category 1***· * Data compared to the previous version altered.**

GB