

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 24.01.2022

Version number 5 (replaces version 4)

Revision: 24.01.2022

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1 Product identifier

Trade name: **DUPLI-COLOR REPAIR SPRAY white 400ml**

Article number: 400215

##### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

##### Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9a Coatings and paints, thinners, paint removers

##### Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

Application of the substance / the mixture Lacquer

##### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

European Aerosols GmbH\*

Kurt Vogelsang Strasse 6

D-74855 Haßmersheim

Tel.: +49 (0) 6266 750

e-mail: sds-de@european-aerosols.com

\*Formerly known as Motip Dupli GmbH

Further information obtainable from: Department Product Safety

##### 1.4 Emergency telephone number:

Tel.: +49 6266-75-310

Fax +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

UK:

Public emergency phone no: 111

Only for healthcare professionals: 0344 892 0111

Ireland:

Poison center if child has been poisoned: 01 809 2166 (8:00 am - 10:00 pm, 7 days)

Only for healthcare professionals: 01 809 2566 (24 h / 7 days)

Tox Info Suisse 145 (24-h-emergency number)

#### SECTION 2: Hazards identification

##### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



(Contd. on page 2)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 24.01.2022

Version number 5 (replaces version 4)

Revision: 24.01.2022

**Trade name: DUPLI-COLOR REPAIR SPRAY white 400ml**

(Contd. of page 1)

Eye Irrit. 2 H319 Causes serious eye irritation.  
 STOT SE 3 H336 May cause drowsiness or dizziness.

### · 2.2 Label elements

#### · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

#### · Hazard pictograms



GHS02 GHS07

#### · Signal word Danger

#### · Hazard-determining components of labelling:

acetone

n-butyl acetate

2-methoxy-1-methylethyl acetate

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

#### · Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

### · 2.3 Other hazards

#### · Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

### · 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

#### · Dangerous components:

|                            |                                     |         |
|----------------------------|-------------------------------------|---------|
| CAS: 67-64-1               | acetone                             | 25-<50% |
| EINECS: 200-662-2          | Flam. Liq. 2, H225                  |         |
| Index number: 606-001-00-8 | Eye Irrit. 2, H319; STOT SE 3, H336 |         |
| Reg.nr.: 01-2119471330-49  | EUH066                              |         |

(Contd. on page 3)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 24.01.2022

Version number 5 (replaces version 4)

Revision: 24.01.2022

**Trade name: DUPLI-COLOR REPAIR SPRAY white 400ml**

(Contd. of page 2)

|   |  |           |
|---|--|-----------|
| CAS: 115-10-6<br>EINECS: 204-065-8<br>Index number: 603-019-00-8<br>Reg.nr.: 01-2119472128-37       | dimethyl ether<br>Flam. Gas 1A, H220<br>Press. Gas (Comp.), H280   | 12.5-<20% |
| CAS: 74-98-6<br>EINECS: 200-827-9<br>Index number: 601-003-00-5<br>Reg.nr.: 01-2119486944-21        | propane<br>Flam. Gas 1A, H220<br>Press. Gas (Comp.), H280  | 10-<12.5% |
| CAS: 106-97-8<br>EINECS: 203-448-7<br>Index number: 601-004-00-0<br>Reg.nr.: 01-2119474691-32       | butane (containing < 0,1 % butadiene (203-450-8))<br>Flam. Gas 1A, H220<br>Press. Gas (Comp.), H280  | 5-<10%    |
| CAS: 123-86-4<br>EINECS: 204-658-1<br>Index number: 607-025-00-1<br>Reg.nr.: 01-2119485493-29       | n-butyl acetate<br>Flam. Liq. 3, H226<br>STOT SE 3, H336<br>EUH066   | 5-<10%    |
| CAS: 108-65-6<br>EINECS: 203-603-9<br>Index number: 607-195-00-7<br>Reg.nr.: 01-2119475791-29       | 2-methoxy-1-methylethyl acetate<br>Flam. Liq. 3, H226<br>STOT SE 3, H336   | 5-<10%    |
| CAS: 75-28-5<br>EINECS: 200-857-2<br>Index number: 601-004-00-0<br>Reg.nr.: 01-2119485395-27        | isobutane (containing < 0,1 % butadiene (203-450-8))<br>Flam. Gas 1A, H220<br>Press. Gas (Comp.), H280   | 2.5-<5%   |
| CAS: 9004-70-0  | cellulose nitrate<br>Flam. Sol. 1, H228  | 2.5-<5%   |
| EC number: 905-588-0<br>Index number: 601-022-00-9<br>Reg.nr.: 01-2119488216-32                     | xylene<br>Flam. Liq. 3, H226<br>STOT RE 2, H373; Asp. Tox. 1, H304<br>Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | <2.5%     |
| CAS: 7429-90-5<br>EINECS: 231-072-3<br>Index number: 013-002-00-1<br>Reg.nr.: 01-2119529243-45-xxxx | aluminium powder (stabilised)<br>Flam. Sol. 2, H228  | <2.5%     |
| CAS: 64-17-5<br>EINECS: 200-578-6<br>Index number: 603-002-00-5<br>Reg.nr.: 01-2119457610-43        | ethanol<br>Flam. Liq. 2, H225<br>Eye Irrit. 2, H319<br>Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %  | <2.5%     |
| CAS: 13463-67-7<br>EINECS: 236-675-5<br>Index number: 022-006-00-2<br>Reg.nr.: 01-2119489379-17     | titanium dioxide<br>Carc. 2, H351  | <2.5%     |

**Additional information:**

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.

xylene: Contains ethylbenzene CAS 100-41-4

For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.

(Contd. on page 4)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 24.01.2022

Version number 5 (replaces version 4)

Revision: 24.01.2022

**Trade name: DUPLI-COLOR REPAIR SPRAY white 400ml**

(Contd. of page 3)

- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.  
Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters -**
- **Protective equipment:** Mouth respiratory protective device.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.  
Keep away from ignition sources.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 2 B
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 5)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 24.01.2022

Version number 5 (replaces version 4)

Revision: 24.01.2022

Trade name: **DUPLI-COLOR REPAIR SPRAY white 400ml**

(Contd. of page 4)

### SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

##### · Ingredients with limit values that require monitoring at the workplace:

###### 67-64-1 acetone

WEL Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppm  
Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

###### 115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m<sup>3</sup>, 500 ppm  
Long-term value: 766 mg/m<sup>3</sup>, 400 ppm

###### 106-97-8 butane (containing < 0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm  
Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm  
Carc (if more than 0.1% of buta-1.3-diene)

###### 123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

###### 108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 274 mg/m<sup>3</sup>, 50 ppm  
Sk

###### xylene

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 220 mg/m<sup>3</sup>, 50 ppm  
Sk; BMGV

###### 64-17-5 ethanol

WEL Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm

##### · Ingredients with biological limit values:

###### xylene

BMGV 650 mmol/mol creatinine  
Medium: urine  
Sampling time: post shift  
Parameter: methyl hippuric acid

· **Additional information:** The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Avoid contact with the eyes.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

(Contd. on page 6)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 24.01.2022

Version number 5 (replaces version 4)

Revision: 24.01.2022

**Trade name: DUPLI-COLOR REPAIR SPRAY white 400ml**

(Contd. of page 5)

**· Hand protection**

Protective gloves

**· Material of gloves**

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

**· Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

**· Eye/face protection**

Tightly sealed goggles

## SECTION 9: Physical and chemical properties

**· 9.1 Information on basic physical and chemical properties****· General Information****· Physical state**

Aerosol

**· Colour:**

According to product specification

**· Odour:**

Characteristic

**· Odour threshold:**

Not determined.

**· Melting point/freezing point:**

Undetermined.

**· Boiling point or initial boiling point and boiling range**

Not applicable, as aerosol.

**· Flammability**

Not applicable.

**· Lower and upper explosion limit****· Lower:**

1.7 Vol %

**· Upper:**

26.2 Vol %

**· Flash point:**

Not applicable, as aerosol.

**· Decomposition temperature:**

Not determined.

**· pH**

Mixture is non-soluble (in water).

**· Viscosity:****· Kinematic viscosity**

Not determined.

**· Dynamic:**

Not determined.

**· Solubility****· water:**

Not miscible or difficult to mix.

**· Partition coefficient n-octanol/water (log value)**

Not determined.

**· Vapour pressure at 20 °C (68 °F):**

8300 hPa (6225.5 mm Hg)

**· Density and/or relative density****· Density at 20 °C (68 °F):**0.7 g/cm<sup>3</sup> (5.8 lbs/gal)**· Relative density**

Not determined.

**· Vapour density**

Not determined.

(Contd. on page 7)

GB



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 24.01.2022

Version number 5 (replaces version 4)

Revision: 24.01.2022

**Trade name: DUPLI-COLOR REPAIR SPRAY white 400ml**

(Contd. of page 6)

**· 9.2 Other information****· Appearance:****· Form:**

Aerosol

**· Important information on protection of health and environment, and on safety.****· Ignition temperature:**

240 °C (464 °F)

**· Explosive properties:**

Not determined.

**· Solvent content:****· Organic solvents:**

91.0 %

**· VOC (EC)**

---

637.1 g/l

**· VOC-EU%**

91.01 %

**· Solids content:**

7.7 %

**· Change in condition****· Evaporation rate**

Not applicable.

**· Information with regard to physical hazard classes****· Explosives**

Void

**· Flammable gases**

Void

**· Aerosols**Extremely flammable aerosol. Pressurised container:  
May burst if heated.**· Oxidising gases**

Void

**· Gases under pressure**

Void

**· Flammable liquids**

Void

**· Flammable solids**

Void

**· Self-reactive substances and mixtures**

Void

**· Pyrophoric liquids**

Void

**· Pyrophoric solids**

Void

**· Self-heating substances and mixtures**

Void

**· Substances and mixtures, which emit flammable gases in contact with water**

Void

**· Oxidising liquids**

Void

**· Oxidising solids**

Void

**· Organic peroxides**

Void

**· Corrosive to metals**

Void

**· Desensitised explosives**

Void

**SECTION 10: Stability and reactivity****· 10.1 Reactivity** No further relevant information available.**· 10.2 Chemical stability****· Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.**· 10.3 Possibility of hazardous reactions** No dangerous reactions known.**· 10.4 Conditions to avoid** No further relevant information available.**· 10.5 Incompatible materials:** No further relevant information available.**· 10.6 Hazardous decomposition products:** No dangerous decomposition products known.**SECTION 11: Toxicological information****· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****· Acute toxicity****· LD/LC50 values relevant for classification:****67-64-1 acetone**

|        |      |                       |
|--------|------|-----------------------|
| Oral   | LD50 | 5800 mg/kg (rat)      |
| Dermal | LD50 | >15800 mg/kg (rabbit) |

(Contd. on page 8)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 24.01.2022

Version number 5 (replaces version 4)

Revision: 24.01.2022

**Trade name: DUPLI-COLOR REPAIR SPRAY white 400ml**

(Contd. of page 7)

|   |            |                                |
|---|------------|--------------------------------|
| Inhalative                                      | LC50 / 4h  | 76 mg/l (rat)                  |
| <b>123-86-4 n-butyl acetate</b>                 |            |                                |
| Oral  | LD50       | 10800 mg/kg (rat) (OECD 401)   |
| Dermal  | LD50       | >17600 mg/kg (rabbit)          |
| Inhalative                                      | LC50 / 4 h | >21 mg/m <sup>3</sup> (rat)    |
| <b>108-65-6 2-methoxy-1-methylethyl acetate</b> |            |                                |
| Oral  | LD50       | 8530 mg/kg (rat)               |
| Dermal  | LD50       | >5000 mg/kg (rabbit)           |
| Inhalative                                      | LC50 / 4 h | >10000 mg/m <sup>3</sup> (rat) |
| <b>xylene</b>                                   |            |                                |
| Oral  | LD50       | 3523 mg/kg (rat)               |
| Dermal  | LD50       | 2000 mg/kg (rabbit)            |
| Inhalative                                      | LC50 / 4 h | 29000 mg/m <sup>3</sup> (rat)  |
| <b>64-17-5 ethanol</b>                          |            |                                |
| Oral  | LD50       | 10470 mg/kg (rat)              |
| Dermal  | LD50       | >2000 mg/kg (rat)              |
| Inhalative                                      | LC50 / 4h  | 120 mg/l (rat)                 |

- **Skin corrosion/irritation** No irritant effect.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

## SECTION 12: Ecological information

### • 12.1 Toxicity

#### • Aquatic toxicity:

##### **67-64-1 acetone**

|             |                                     |
|-------------|-------------------------------------|
| LC50/96h    | 8300 mg/l (fish)                    |
| EC50/96h    | 7200 mg/l (algae)                   |
| LC50 / 48 h | 8450 mg/l (crustacean (water flea)) |

##### **115-10-6 dimethyl ether**

|             |                            |
|-------------|----------------------------|
| EC50 / 96 h | 155 mg/l (algae)           |
| LC50 / 48 h | >4000 mg/l (daphnia magna) |
| LC50 / 96 h | >4000 mg/l (fish)          |

##### **108-65-6 2-methoxy-1-methylethyl acetate**

|             |  |
|-------------|--|
| EC50 / 48 h | >500 mg/l (daphnia magna)                              |
| LC50 / 96 h | 100-180 mg/l (oncorhynchus mykiss / Regenbogenforelle) |

##### **xylene**

|             |                          |
|-------------|--------------------------|
| EC50 / 48 h | 7.4 mg/l (daphnia magna) |
| LC50 / 96 h | 13.5 mg/l (fish)         |

##### **64-17-5 ethanol**

|             |  |
|-------------|--|
| LC50/96h    | 13000 mg/l (oncorhynchus mykiss / Regenbogenforelle) |
| EC50 / 48 h | 12900 mg/l (algae)                                   |
| LC50 / 48 h | 12340 mg/l (daphnia magna)                           |

(Contd. on page 9)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 24.01.2022

Version number 5 (replaces version 4)

Revision: 24.01.2022

**Trade name: DUPLI-COLOR REPAIR SPRAY white 400ml**



(Contd. of page 8)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**  
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:**  
Disposal must be made according to official regulations.  
Disposal must be made according to official regulations.

### SECTION 14: Transport information

- |   |                     |
|---|---------------------|
| · <b>14.1 UN number or ID number</b>  |                     |
| · <b>ADR, IMDG, IATA</b>  | UN1950              |
| · <b>14.2 UN proper shipping name</b>   |                     |
| · <b>ADR</b>  | 1950 AEROSOLS       |
| · <b>IMDG</b>   | AEROSOLS            |
| · <b>IATA</b>   | AEROSOLS, flammable |
| · <b>14.3 Transport hazard class(es)</b>  |                     |
| · <b>ADR</b>  |                     |
|  |                     |
| · <b>Class</b>  | 2 5F Gases.         |
| · <b>Label</b>  | 2.1                 |
| · <b>IMDG, IATA</b>   |                     |
|  |                     |
| · <b>Class</b>  | 2.1 Gases.          |
| · <b>Label</b>  | 2.1                 |
| · <b>14.4 Packing group</b>   |                     |
| · <b>ADR, IMDG, IATA</b>  | not regulated       |
| · <b>14.5 Environmental hazards:</b>  | Not applicable.     |

(Contd. on page 10)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 24.01.2022

Version number 5 (replaces version 4)

Revision: 24.01.2022

**Trade name: DUPLI-COLOR REPAIR SPRAY white 400ml**

(Contd. of page 9)

|   |   |
|---|---|
| <ul style="list-style-type: none"> <li>· <b>14.6 Special precautions for user</b></li> <li>· <b>Hazard identification number (Kemler code):</b></li> <li>· <b>EMS Number:</b></li> <li>· <b>Stowage Code</b></li> </ul> | <p>Warning: Gases.</p> <p>-</p> <p>F-D,S-U</p> <p>SW1 Protected from sources of heat.</p> <p>SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.</p> <p>SG69 For AEROSOLS with a maximum capacity of 1 litre:</p> <p>Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.</p> <p>For AEROSOLS with a capacity above 1 litre:</p> <p>Segregation as for the appropriate subdivision of class 2.</p> <p>For WASTE AEROSOLS:</p> <p>Segregation as for the appropriate subdivision of class 2.</p> |
| <ul style="list-style-type: none"> <li>· <b>14.7 Maritime transport in bulk according to IMO instruments</b></li> </ul>   | <p>Not applicable.</p>  |
| <ul style="list-style-type: none"> <li>· <b>Transport/Additional information:</b></li> </ul>  |   |
| <ul style="list-style-type: none"> <li>· <b>ADR</b></li> <li>· <b>Limited quantities (LQ)</b></li> <li>· <b>Excepted quantities (EQ)</b></li> </ul>   | <p>1L</p> <p>Code: E0</p> <p>Not permitted as Excepted Quantity</p>   |
| <ul style="list-style-type: none"> <li>· <b>Transport category</b></li> <li>· <b>Tunnel restriction code</b></li> </ul>   | <p>2</p> <p>D</p>   |
| <ul style="list-style-type: none"> <li>· <b>IMDG</b></li> <li>· <b>Limited quantities (LQ)</b></li> <li>· <b>Excepted quantities (EQ)</b></li> </ul>  | <p>1L</p> <p>Code: E0</p> <p>Not permitted as Excepted Quantity</p>   |
| <ul style="list-style-type: none"> <li>· <b>UN "Model Regulation":</b></li> </ul>   | <p>UN 1950 AEROSOLS, 2.1</p>  |

\*

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a** FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **National regulations:**
- **Information about limitation of use:**

· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients is listed.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
- H220 Extremely flammable gas.

(Contd. on page 11)

GB

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 24.01.2022

Version number 5 (replaces version 4)

Revision: 24.01.2022

**Trade name: DUPLI-COLOR REPAIR SPRAY white 400ml**

(Contd. of page 10)

- H225 *Highly flammable liquid and vapour.*  
 H226 *Flammable liquid and vapour.*  
 H228 *Flammable solid.*  
 H280 *Contains gas under pressure; may explode if heated.*  
 H304 *May be fatal if swallowed and enters airways.*  
 H312 *Harmful in contact with skin.*  
 H315 *Causes skin irritation.*  
 H319 *Causes serious eye irritation.*  
 H332 *Harmful if inhaled.*  
 H335 *May cause respiratory irritation.*  
 H336 *May cause drowsiness or dizziness.*  
 H351 *Suspected of causing cancer.*  
 H373 *May cause damage to organs through prolonged or repeated exposure.*  
 EUH066 *Repeated exposure may cause skin dryness or cracking.*

**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
 IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
 ICAO: International Civil Aviation Organisation  
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)  
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 SVHC: Substances of Very High Concern  
 vPvB: very Persistent and very Bioaccumulative  
 Flam. Gas 1A: Flammable gases – Category 1A  
 Aerosol 1: Aerosols – Category 1  
 Press. Gas (Comp.): Gases under pressure – Compressed gas  
 Flam. Liq. 2: Flammable liquids – Category 2  
 Flam. Liq. 3: Flammable liquids – Category 3  
 Flam. Sol. 1: Flammable solids – Category 1  
 Flam. Sol. 2: Flammable solids – Category 2  
 Acute Tox. 4: Acute toxicity – Category 4  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
 Carc. 2: Carcinogenicity – Category 2  
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
 Asp. Tox. 1: Aspiration hazard – Category 1

**\* Data compared to the previous version altered.**

GB