

Page 1/10

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.05.2022 Version number 84 (replaces version 83) Revision: 30.03.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: PRESTO LABEL REMOVER 500 ML
- · Article number: 365638
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category Flux agents for casting
- · Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

- · Application of the substance / the mixture Cleaning agent/ Cleaner
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

European Aerosols B.V.\*

Wolfraamweg 2

NL-8471 XC Wolvega

The Netherlands

Tel: +31 (0)561 694400

e-mail: sds-nl@european-aerosols.com

- \*Formerly known as Motip Dupli B.V.
- · Further information obtainable from: Department Product Safety
- · 1.4 Emergency telephone number:

+31 (0)561-694400 (09:00h - 17:00h)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



.

flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



• environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.

(Contd. on page 2)

Version number 84 (replaces version 83) Revision: 30.03.2022 Printing date 30.05.2022

Trade name: PRESTO LABEL REMOVER 500 ML

(Contd. of page 1)

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms







GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

(R)-p-mentha-1,8-diene

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

· Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 5989-27-5	(R)-p-mentha-1,8-diene	50-<75%
EINECS: 227-813-5	♠ Flam. Liq. 3, H226	
Index number: 601-029-00-7	& Asp. Tox. 1, H304	
Reg.nr.: 01-2119529223-47	🚯 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
	(1) Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317	
CAS: 74-98-6	propane	10-<12.5%
EINECS: 200-827-9	📀 Flam. Gas 1A, H220	
Index number: 601-003-00-5	Press. Gas (Comp.), H280	
Reg.nr.: 01-2119486944-21		
CAS: 106-97-8	butane (containing < 0,1 % butadiene (203-450-8))	5-<10%
EINECS: 203-448-7	🚸 Flam. Gas 1A, H220	
Index number: 601-004-00-0	Press. Gas (Comp.), H280	
Reg.nr.: 01-2119474691-32		Contd. on maga 2)

(Contd. on page 3)

Printing date 30.05.2022 Version number 84 (replaces version 83) Revision: 30.03.2022

Trade name: PRESTO LABEL REMOVER 500 ML

		(Contd. of page
CAS: 75-28-5	isobutane (containing $< 0.1 \%$ butadiene (203-450-8))	5-<10%
EINECS: 200-857-2	🚸 Flam. Gas 1A, H220	
Index number: 601-004-00-0		
Reg.nr.: 01-2119485395-27	• "	
· Regulation (EC) No 648/200	4 on detergents / Labelling for contents	
perfumes (Limonene)		≥30%
aliphatic hydrocarbons		≥15 - <30%
· Additional information: For	the wording of the listed hazard phrases refer to section 16.	

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

Printing date 30.05.2022 Version number 84 (replaces version 83) Revision: 30.03.2022

Trade name: PRESTO LABEL REMOVER 500 ML

(Contd. of page 3)

No special measures required.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

#### 106-97-8 butane (containing < 0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· Hand protection



Protective gloves

#### · Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

#### · Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min

(Contd. on page 5)

Printing date 30.05.2022 Version number 84 (replaces version 83) Revision: 30.03.2022

Trade name: PRESTO LABEL REMOVER 500 ML

(Contd. of page 4)

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42-480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· Eye/face protection Not required.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:

Aerosol
Clear
Fruit-like
Not determined.
Undetermined.

· Boiling point or initial boiling point and boiling

range Not applicable, as aerosol.

· Flammability Not applicable.

· Lower and upper explosion limit

• **Lower:** 0.7 Vol % (5989-27-5 (R)-p-mentha-1,8-diene)

Upper: 10.9 Vol % (74-98-6 propane)
Flash point: Not applicable, as aerosol.

• Ignition temperature: 245 °C (473 °F) (5989-27-5 (R)-p-mentha-1,8-diene)

• Decomposition temperature: Not determined. • pH Not determined.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

· Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

• Vapour pressure at 20 °C (68 °F): 3500 hPa (2625.2 mm Hg)

· Density and/or relative density

Density at 20 °C (68 °F):
 Relative density
 Vapour density
 Not determined.
 Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health and

environment, and on safety.

· Explosive properties: Not determined.

· Solvent content:

· Organic solvents: 100.0 % · VOC (EC) ---

737.0 g/l
• VOC-EU% 100.00 %
• Solids content: 0.0 %

· Change in condition

• Evaporation rate Not applicable.

· Information with regard to physical hazard classes

Explosives VoidFlammable gases Void

· Aerosols Extremely flammable aerosol. Pressurised container:

May burst if heated.

(Contd. on page 6)

Printing date 30.05.2022 Version number 84 (replaces version 83) Revision: 30.03.2022

Trade name: PRESTO LABEL REMOVER 500 ML

		(Contd. of page 5)
· Oxidising gases	Void	
· Gases under pressure	Void	
· Flammable liquids	Void	
· Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
· Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamma	ble	
gases in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity
- · LD/LC50 values relevant for classification:

### 5989-27-5 (R)-p-mentha-1,8-diene

 Oral
 LD50
 2000 mg/kg (rat)

 Dermal
 LD50
 >5000 mg/kg (rabbit)

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

### 5989-27-5 (R)-p-mentha-1,8-diene

EC50 / 48 h | 0.36 mg/l (daphnia magna)

EC50 / 72 h 150 mg/l (algae)

EC50/72h | 0.72 mg/l (fish)

LC50 / 72 h | 0.72 mg/l (fish)

(Contd. on page 7)

Version number 84 (replaces version 83) Revision: 30.03.2022 Printing date 30.05.2022

Trade name: PRESTO LABEL REMOVER 500 ML

(Contd. of page 6)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Very toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Disposal must be made according to official regulations.

### SECTION 14: Transport information

· 14.1 UN number or ID number

UN1950 · ADR, IMDG, IATA

· 14.2 UN proper shipping name

1950 AEROSOLS, ENVIRONMENTALLY  $\cdot ADR$ 

**HAZARDOUS** 

· IMDG AEROSOLS, MARINE POLLUTANT

AEROSOLS, flammable

- · 14.3 Transport hazard class(es)
- $\cdot ADR$

 $\cdot$  IATA



2 5F Gases. · Class 2.1

· Label

· IMDG



· Class 2.1 Gases.

(Contd. on page 8)

Printing date 30.05.2022 Version number 84 (replaces version 83) Revision: 30.03.2022

Trade name: PRESTO LABEL REMOVER 500 ML

	(Contd. of page
Label	2.1
IATA	
2	
Class	2.1 Gases.
Label	2.1 Gases. 2.1
	2.1
14.4 Packing group ADR, IMDG, IATA	not regulated
* * *	noi regulatea
14.5 Environmental hazards: Marine pollutant:	Yes
marine politicali.	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Gases.
Hazard identification number (Kemler code):	-
EMS Number:	F- $D$ , $S$ - $U$
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1
	litre: Category A. For AEROSOLS with a capacity
	above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1
Segregation Code	litre:
	Segregation as for class 9. Stow "separated from" class
	1 except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of clas
	2. For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of clas
	2.
14.7 Maritime transport in bulk according to II	MO
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities $(\widetilde{EQ})$	Code: E0
	Not permitted as Excepted Quantity
	Code: E0
Transport category	Not permitted as Excepted Quantity 2
	D D
Tunnel restriction code	
Tunnel restriction code IMDG	
Tunnel restriction code  IMDG  Limited quantities (LQ)	1L
Tunnel restriction code  IMDG  Limited quantities (LQ)  Excepted quantities (EQ)	1L Code: E0
Tunnel restriction code  IMDG  Limited quantities (LQ)	IL.

Printing date 30.05.2022 Version number 84 (replaces version 83) Revision: 30.03.2022

Trade name: PRESTO LABEL REMOVER 500 ML

(Contd. of page 8)

· UN ''Model Regulation'':

UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY

*HAZARDOUS* 

### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E1 Hazardous to the Aquatic Environment

P3a FLAMMABLE AEROSOLS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

- · Department issuing SDS: R&D legislation and regulatory advisor
- · Contact: e-mail: sds-nl@european-aerosols.com
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

(Contd. on page 10)

Page 10/10

# Safety data sheet according to 1907/2006/EC, Article 31

Version number 84 (replaces version 83) Printing date 30.05.2022 Revision: 30.03.2022

Trade name: PRESTO LABEL REMOVER 500 ML

(Contd. of page 9)

Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

\* Data compared to the previous version altered.