

Page 1/9

*

*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.05.2022

Version number 4 (replaces version 3)

Revision: 20.05.2022

SECTION 1:	Identifica	tion of the substance/mixture and of the company/undertaking
1.1 Product ide	ntifier	
Trade name: P	RESTO CAB	BLE CLISS SPRAY 400 ML
No further releve Sector of Use SU21 Consum SU22 Professi Product catego Process catego PROC7 Indust PROC11 Non	entified uses vant informat er uses: Priva onal uses: Pu ry Other coat ry trial spraying industrial spr	rate households / general public / consumers ublic domain (administration, education, entertainment, services, craftsmen) tings and paints
Manufacturer/S European Aero. Wolfraamweg 2 NL-8471 XC W The Netherland Tel : +31 (0)56 e-mail: sds-nl@ *Formerly know Further inform 1.4 Emergency +31 (0)561-694	Supplier: sols B.V.* olvega l 694400 european-ae vn as Motip L ation obtaina telephone nu 400 (09:00h	Dupli B.V. able from: Department Product Safety umber:
SECTION 2:	Hazards i	identification
Classification a		ostance or mixture Regulation (EC) No 1272/2008
flame	2	
Aerosol 1		229 Extremely flammable aerosol. Pressurised container: May burst if heated.
Aerosol 1		229 Extremely flammable aerosol. Pressurised container: May burst if heated.
Aerosol 1	H222-H2 conment	229 Extremely flammable aerosol. Pressurised container: May burst if heated. Toxic to aquatic life with long lasting effects.
Aerosol 1	H222-H2 conment	
Aerosol 1 Aerosol 1 envir Aquatic Chroni	H222-H2 conment c 2 H411	Toxic to aquatic life with long lasting effects.

Page 2/9


Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.05.2022

Version number 4 (replaces version 3)

Revision: 20.05.2022

Trade name: PRESTO CABLE CLISS SPRAY 400 ML



- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components: EC number: 927-510-4 Naphtha (petroleum), hydrotreated light 25-<50% Reg.nr.: 01-2119475515-33 🚸 Flam. Liq. 2, H225 🚯 Asp. Tox. 1, H304 🚯 Aquatic Chronic 2, H411 🚯 Skin Irrit. 2, H315; STOT SE 3, H336 CAS: 74-98-6 20-<25% propane EINECS: 200-827-9 🚸 Flam. Gas 1A, H220 Index number: 601-003-00-5 Press. Gas (Comp.), H280 Reg.nr.: 01-2119486944-21 (Contd. on page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.05.2022

Version number 4 (replaces version 3)

Revision: 20.05.2022

Trade name: PRESTO CABLE CLISS SPRAY 400 ML

		(Contd. of page 2)
CAS: 106-97-8	butane (containing $< 0,1$ % butadiene (203-450-8))	12.5-<20%
EINECS: 203-448-7	🚸 Flam. Gas 1A, H220	
Index number: 601-004-00-0	Press. Gas (Comp.), H280	
Reg.nr.: 01-2119474691-32		
CAS: 75-28-5	isobutane (containing < 0,1 % butadiene (203-450-8))	12.5-<20%
EINECS: 200-857-2	🚸 Flam. Gas 1A, H220	
Index number: 601-004-00-0		
Reg.nr.: 01-2119485395-27		
. Additional information: For	the wording of the listed bazard phrases refer to section 16	· · · · · · · · · · · · · · · · · · ·

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• After inhalation: In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- \cdot 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away. Keep away from ignition sources.
 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
 6.4 Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

- · Information about fire and explosion protection:
- Do not spray onto a naked flame or any incandescent material.

(Contd. on page 4)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.05.2022

Version number 4 (replaces version 3)

Revision: 20.05.2022

Trade name: PRESTO CABLE CLISS SPRAY 400 ML

(Contd. of page 3)

Keep ignition sources away - Do not smoke. Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane (containing < 0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the skin. Avoid contact with the eyes and skin.
- · Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3
• Hand protection



Protective gloves

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

 \cdot Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to: Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length

of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

(Contd. on page 5)

Page 5/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.05.2022

Version number 4 (replaces version 3)

Revision: 20.05.2022

(Contd. of page 4)

Trade name: PRESTO CABLE CLISS SPRAY 400 ML

• Eye/face protection Not required.

ties psol purless pent-like determined. letermined. letermined. applicable, as aerosol. applicable. Vol % (Naphtha (petroleum), hydrotreated light) Vol % (74-98-6 propane) applicable, as aerosol. 0 °C (>446 °F) (Naphtha (petroleum), rotreated light) determined. ture is non-soluble (in water). determined. determined. miscible or difficult to mix. determined. 0 hPa (2625.2 mm Hg)
psol purless pent-like determined. determined. applicable, as aerosol. applicable. Vol % (Naphtha (petroleum), hydrotreated light) Vol % (74-98-6 propane) applicable, as aerosol. 0 °C (>446 °F) (Naphtha (petroleum), rotreated light) determined. ture is non-soluble (in water). determined. determined. determined. determined. D hPa (2625.2 mm Hg)
purless pent-like determined. letermined. applicable, as aerosol. applicable. Vol % (Naphtha (petroleum), hydrotreated light) Vol % (74-98-6 propane) applicable, as aerosol. 0 °C (>446 °F) (Naphtha (petroleum), rotreated light) determined. ture is non-soluble (in water). determined. determined. determined. determined. D hPa (2625.2 mm Hg)
purless pent-like determined. letermined. applicable, as aerosol. applicable. Vol % (Naphtha (petroleum), hydrotreated light) Vol % (74-98-6 propane) applicable, as aerosol. 0 °C (>446 °F) (Naphtha (petroleum), rotreated light) determined. ture is non-soluble (in water). determined. determined. determined. determined. D hPa (2625.2 mm Hg)
eent-like determined. letermined. applicable, as aerosol. applicable. Vol % (Naphtha (petroleum), hydrotreated light) Vol % (74-98-6 propane) applicable, as aerosol. 0 °C (>446 °F) (Naphtha (petroleum), rotreated light) determined. ture is non-soluble (in water). determined. determined. determined. miscible or difficult to mix. determined. 0 hPa (2625.2 mm Hg)
determined. letermined. applicable, as aerosol. applicable. Vol % (Naphtha (petroleum), hydrotreated light) Vol % (74-98-6 propane) applicable, as aerosol. 0 °C (>446 °F) (Naphtha (petroleum), rotreated light) determined. ture is non-soluble (in water). determined. determined. miscible or difficult to mix. determined. D hPa (2625.2 mm Hg)
Tetermined. applicable, as aerosol. applicable. Vol % (Naphtha (petroleum), hydrotreated light) Vol % (74-98-6 propane) applicable, as aerosol. 0 °C (>446 °F) (Naphtha (petroleum), rotreated light) determined. ture is non-soluble (in water). determined. determined. determined. 0 hPa (2625.2 mm Hg)
applicable, as aerosol. applicable. Vol % (Naphtha (petroleum), hydrotreated light) Vol % (74-98-6 propane) applicable, as aerosol. 0 °C (>446 °F) (Naphtha (petroleum), rotreated light) determined. ture is non-soluble (in water). determined. determined. determined. 0 hPa (2625.2 mm Hg)
applicable. Vol % (Naphtha (petroleum), hydrotreated light) Vol % (74-98-6 propane) applicable, as aerosol. 0 °C (>446 °F) (Naphtha (petroleum), rotreated light) determined. ture is non-soluble (in water). determined. determined. miscible or difficult to mix. determined. D hPa (2625.2 mm Hg)
applicable. Vol % (Naphtha (petroleum), hydrotreated light) Vol % (74-98-6 propane) applicable, as aerosol. 0 °C (>446 °F) (Naphtha (petroleum), rotreated light) determined. ture is non-soluble (in water). determined. determined. miscible or difficult to mix. determined. D hPa (2625.2 mm Hg)
 Vol % (Naphtha (petroleum), hydrotreated light) Vol % (74-98-6 propane) applicable, as aerosol. 0 °C (>446 °F) (Naphtha (petroleum), rotreated light) determined. ture is non-soluble (in water). determined. determined. determined. determined. miscible or difficult to mix. determined. 0 hPa (2625.2 mm Hg)
 Vol % (74-98-6 propane) applicable, as aerosol. 0 °C (>446 °F) (Naphtha (petroleum), rotreated light) determined. ture is non-soluble (in water). determined. determined. miscible or difficult to mix. determined. D hPa (2625.2 mm Hg)
 Vol % (74-98-6 propane) applicable, as aerosol. 0 °C (>446 °F) (Naphtha (petroleum), rotreated light) determined. ture is non-soluble (in water). determined. determined. miscible or difficult to mix. determined. D hPa (2625.2 mm Hg)
applicable, as aerosol. 0 °C (>446 °F) (Naphtha (petroleum), rotreated light) determined. ture is non-soluble (in water). determined. determined. miscible or difficult to mix. determined. 0 hPa (2625.2 mm Hg)
0°C (>446°F) (Naphtha (petroleum), rotreated light) determined. ture is non-soluble (in water). determined. determined. miscible or difficult to mix. determined. 0 hPa (2625.2 mm Hg)
rotreated light) determined. ture is non-soluble (in water). determined. determined. miscible or difficult to mix. determined. 0 hPa (2625.2 mm Hg)
determined. ture is non-soluble (in water). determined. determined. miscible or difficult to mix. determined. 0 hPa (2625.2 mm Hg)
determined. ture is non-soluble (in water). determined. determined. miscible or difficult to mix. determined. 0 hPa (2625.2 mm Hg)
determined. determined. miscible or difficult to mix. determined. 9 hPa (2625.2 mm Hg)
determined. determined. miscible or difficult to mix. determined. 9 hPa (2625.2 mm Hg)
determined. miscible or difficult to mix. determined.) hPa (2625.2 mm Hg)
determined. miscible or difficult to mix. determined.) hPa (2625.2 mm Hg)
miscible or difficult to mix. determined. 9 hPa (2625.2 mm Hg)
determined. 0 hPa (2625.2 mm Hg)
determined. 0 hPa (2625.2 mm Hg)
0 hPa (2625.2 mm Hg)
g/cm ³ (5 lbs/gal)
determined.
determined.
osol
determined.
0%
%
/0
applicable
applicable.
l
l
emely flammable aerosol. Pressurised container:
burst if heated.
l
l
l
1
l l

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.05.2022

Version number 4 (replaces version 3)

Revision: 20.05.2022

Trade name: PRESTO CABLE CLISS SPRAY 400 ML

		(Contd. of page 5)
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
· Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit flamm	able	
gases in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation No irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.
- · STOT-single exposure May cause drowsiness or dizziness.
- \cdot 11.2 Information on other hazards
- · Endocrine disrupting properties
- None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- · **vPvB**: Not applicable.
- · 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:
- Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.

(Contd. on page 7)

Page 7/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.05.2022

Version number 4 (replaces version 3)

Revision: 20.05.2022


(Contd. of page 6)

Trade name: PRESTO CABLE CLISS SPRAY 400 ML

Toxic for aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- *Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.*
- · Uncleaned packaging:
- · Recommendation:
- Disposal must be made according to official regulations.
- Disposal must be made according to official regulations.



Page 8/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.05.2022

Version number 4 (replaces version 3)

Revision: 20.05.2022

Trade name: PRESTO CABLE CLISS SPRAY 400 ML

	(Contd. of page
Hazard identification number (Kemler code):	-
EMS Number:	F- D , S - U
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1
	litre: Category A. For AEROSOLS with a capacity
	above 1 litre: Category B. For WASTE AEROSOLS:
	Category C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1
	litre:
	Segregation as for class 9. Stow "separated from" clas
	1 except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class
	2.
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class
	2.
14.7 Maritime transport in bulk according to IM	10
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (\widetilde{EQ})	Code: E0
· · · · · ·	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity
UN ''Model Regulation'':	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY
0	HAZARDOUS

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

*

- P3a FLAMMABLE AEROSOLS
- E2 Hazardous to the Aquatic Environment
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· National regulations:

 \cdot Other regulations, limitations and prohibitive regulations

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

(Contd. on page 9)

GB

Page 9/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 31.05.2022

Version number 4 (replaces version 3)

Revision: 20.05.2022

Trade name: PRESTO CABLE CLISS SPRAY 400 ML

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. of page 8)

SECTION 16: Other information This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. · Relevant phrases H220 Extremely flammable gas. H225 Highly flammable liquid and vapour. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. · Department issuing SDS: R&D legislation and regulatory advisor · Contact: e-mail: sds-nl@european-aerosols.com · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A Aerosol 1: Aerosols - Category 1 Press. Gas (Comp.): Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids - Category 2 Skin Irrit. 2: Skin corrosion/irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 \cdot * Data compared to the previous version altered. GB