

Page 1/10

\*

\*

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.07.2022

Version number 34 (replaces version 33)

Revision: 30.03.2022

110 1	: Identification of the substance/mixture and of the company/undertakin
1.1 Product ide	entifier
Trade name: D	DUPLI-COLOR PROFI DEGREASER SPRAY 400 ML
No further releve Sector of Use SU21 Consum SU22 Professi Product catego PROC7 Indust PROC11 Non	lentified uses of the substance or mixture and uses advised against vant information available. her uses: Private households / general public / consumers ional uses: Public domain (administration, education, entertainment, services, craftsmen rry Flux agents for casting ry
Manufacturer/S European Aero Wolfraamweg 2 NL-8471 XC W The Netherland Tel : +31 (0)56 e-mail: sds-nl@ *Formerly know Further inform 1.4 Emergency	osols B.V.* 2 Volvega Is
UK: NPIS Natio	onal Poisons Information Centre Tel: +44 0344 892 0111
	: Hazards identification
2.1 Classificati	ion of the substance or mixture
2.1 Classification	
2.1 Classificati	ion of the substance or mixture according to Regulation (EC) No 1272/2008
2.1 Classification a Classification a flame	ion of the substance or mixture according to Regulation (EC) No 1272/2008 e
2.1 Classification a	ion of the substance or mixture according to Regulation (EC) No 1272/2008
2.1 Classification a Classification a flame Aerosol 1	ion of the substance or mixture according to Regulation (EC) No 1272/2008 e
2.1 Classification a Classification a flame Aerosol 1	ton of the substance or mixture according to Regulation (EC) No 1272/2008 e H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heat ronment
2.1 Classification of Classifi	ton of the substance or mixture according to Regulation (EC) No 1272/2008 e H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heat ronment
2.1 Classification of Classifi	ion of the substance or mixture according to Regulation (EC) No 1272/2008 e H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heat ronment ic 2 H411 Toxic to aquatic life with long lasting effects.
2.1 Classification of Classifi	ton of the substance or mixture according to Regulation (EC) No 1272/2008 e H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heat ronment

Page 2/10

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.07.2022

Version number 34 (replaces version 33)

Revision: 30.03.2022

#### Trade name: DUPLI-COLOR PROFI DEGREASER SPRAY 400 ML



#### **SECTION 3:** Composition/information on ingredients

#### · 3.2 Mixtures

 $\cdot \textit{Description: Mixture of substances listed below with nonhazardous additions.}$ 

· Dangerous components: EC number: 920-750-0 50-<75% Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Reg.nr.: 01-2119473851-33 🐵 Flam. Liq. 2, H225 🚯 Asp. Tox. 1, H304 🚯 Aquatic Chronic 2, H411 (1) STOT SE 3, H336 *EUH066* CAS: 74-98-6 12.5-<20% propane EINECS: 200-827-9 🚸 Flam. Gas 1A, H220 Index number: 601-003-00-5 Press. Gas (Comp.), H280 Reg.nr.: 01-2119486944-21 CAS: 67-63-0 propan-2-ol 10-<12.5% EINECS: 200-661-7 🚸 Flam. Liq. 2, H225 ( Eye Irrit. 2, H319; STOT SE 3, H336 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25 (Contd. on page 3)

Printing date 04.07.2022

Version number 34 (replaces version 33)

Revision: 30.03.2022

#### Trade name: DUPLI-COLOR PROFI DEGREASER SPRAY 400 ML

		(Contd. of page 2)
CAS: 106-97-8	butane (containing $< 0,1$ % butadiene (203-450-8))	5-<10%
EINECS: 203-448-7	🚸 Flam. Gas 1A, H220	-
Index number: 601-004-00-0	Press. Gas (Comp.), H280	
Reg.nr.: 01-2119474691-32		
CAS: 75-28-5	isobutane (containing < 0,1 % butadiene (203-450-8))	5-<10%
EINECS: 200-857-2	🚸 Flam. Gas 1A, H220	-
Index number: 601-004-00-0		
Reg.nr.: 01-2119485395-27		
Additional information: For	the wording of the listed hezard phrases refer to section 16	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- $\cdot$  5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters -
- Protective equipment: Mouth respiratory protective device.

#### **SECTION 6:** Accidental release measures

- $\cdot$  6.1 Personal precautions, protective equipment and emergency procedures
- Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- Keep away from ignition sources.
- 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
   See Section 7 for information on safe handling.
   See Section 8 for information on personal protection equipment.
   See Section 13 for disposal information.

#### **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

- · Information about fire and explosion protection:
- Do not spray onto a naked flame or any incandescent material.

(Contd. on page 4)

ЗB

Printing date 04.07.2022

Version number 34 (replaces version 33)

Revision: 30.03.2022

#### Trade name: DUPLI-COLOR PROFI DEGREASER SPRAY 400 ML

(Contd. of page 3)

Keep ignition sources away - Do not smoke. Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- · Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurised containers.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

#### · Ingredients with limit values that require monitoring at the workplace:

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m<sup>3</sup>, 500 ppm Long-term value: 999 mg/m<sup>3</sup>, 400 ppm

#### 106-97-8 butane (containing < 0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

• Additional information: The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

- Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes and skin.
- Avoid contact with the eyes.
- · Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

### Filter A2/P3 • Hand protection



Protective gloves

• *Material of gloves Butyl rubber, BR* 

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to: Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min

GB

Page 5/10

#### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.07.2022

Version number 34 (replaces version 33)

Revision: 30.03.2022

#### Trade name: DUPLI-COLOR PROFI DEGREASER SPRAY 400 ML

(Contd. of page 4)

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· Eye/face protection



\*

Tightly sealed goggles

	erties
9.1 Information on basic physical and chemical p	roperties
General Information	
Physical state	Aerosol
Colour:	Clear
Odour:	Solvent-like
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling	
range	Not applicable, as aerosol.
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	0.6 Vol % (Hydrocarbons, C7-C9, n-alkanes,
	isoalkanes, cyclics)
Upper:	12 Vol % (67-63-0 propan-2-ol)
Flash point:	Not applicable, as aerosol.
Ignition temperature:	$>200^{\circ}C$ (>392 °F) (Hydrocarbons, C7-C9, n-alkanes
	isoalkanes, cyclics)
Decomposition temperature:	Not determined.
pH	Mixture is non-soluble (in water).
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic:	Not determined.
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 $^{\circ}C$ (68 $^{\circ}F$ ):	3500 hPa (2625.2 mm Hg)
Density and/or relative density	5500 hi a (2023.2 hint 11g)
Density at 20 $^{\circ}C$ (68 $^{\circ}F$ ):	0.7 g/cm <sup>3</sup> (5.8 lbs/gal)
Relative density	Not determined.
Vapour density	Not determined.
тирош исполу	1101 uciel IIIIIleu.
9.2 Other information	
Appearance:	
Form:	Aerosol
Important information on protection of health and	d
environment, and on safety.	
Explosive properties:	Not determined.
Solvent content:	
Organic solvents:	100.0 %
VOC (EC)	
	674.0 g/l
VOC-EU%	100.00 %
Solids content:	0.0%

(Contd. on page 6) GB

Printing date 04.07.2022

Version number 34 (replaces version 33)

Revision: 30.03.2022

#### Trade name: DUPLI-COLOR PROFI DEGREASER SPRAY 400 ML

	(Contd. of page
Change in condition	
Evaporation rate	Not applicable.
Information with regard to physical hazard o	classes
Explosives	Void
Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised container:
	May burst if heated.
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
· Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flamm	able
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
· Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

#### **SECTION 11: Toxicological information**

- $\cdot$  11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

· LD/LC50 values relevant for classification:		
67-63-0 propan-2-ol		
Oral	LD50	5840 mg/kg (rat)
Dermal	LD50	13900 mg/kg (rabbit)
Inhalative	LC50	>25 mg/l (rat) LC 50: 6h
<ul> <li>Skin corrosion/irritation No irritant effect.</li> <li>Serious eye damage/irritation Causes serious eye irritation.</li> <li>Respiratory or skin sensitisation No sensitising effects known.</li> <li>STOT-single exposure May cause drowsiness or dizziness.</li> <li>11.2 Information on other hazards</li> </ul>		
· Endocrine disrupting properties		
None of the ingredients is listed.		
GB		

(Contd. on page 7)

Printing date 04.07.2022

Version number 34 (replaces version 33)

Revision: 30.03.2022

Trade name: DUPLI-COLOR PROFI DEGREASER SPRAY 400 ML

(Contd. of page 6)

#### SECTION 12: Ecological information

•	12.1	Toxicity
---	------	----------

- Aquatic toxicity:
- 67-63-0 propan-2-ol

LC50/96h 9640 mg/l (pimephales promelas; 96h)

LC50 / 24 h 9714 mg/l (daphnia magna)

· 12.2 Persistence and degradability No further relevant information available.

- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms.

Toxic for aquatic organisms

#### **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations. Disposal must be made according to official regulations.

14.1 UN number or ID number ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR	1950 AEROSOLS, ENVIRONMENTALLY
	HAZARDOUS
IMDG	AEROSOLS, MARINE POLLUTANT
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	

Page 8/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.07.2022

Version number 34 (replaces version 33)

Revision: 30.03.2022

#### Trade name: DUPLI-COLOR PROFI DEGREASER SPRAY 400 ML

	(Contd. of pa
Label	2.1
Class	2.1 Gases.
Label	2.1
Class	2.1 Gases.
Label	2.1
14.4 Packing group ADR, IMDG, IATA	not regulated
14.5 Environmental hazards:	
Marine pollutant: Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
	• •
14.6 Special precautions for user	Warning: Gases.
Hazard identification number (Kemler code): EMS Number:	- F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
0	SW22 For AEROSOLS with a maximum capacity of I
	litre: Category A. For AEROSOLS with a capacity
	above 1 litre: Category B. For WASTE AEROSOLS:
Sagragation Code	Category C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre:
	Segregation as for class 9. Stow "separated from" cla
	<i>1 except for division 1.4.</i>
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of cla
	2. For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of cla
	2.
14.7 Maritime transport in bulk according to IM	0
instruments	Not applicable.
Transport/Additional information:	
ADR Limited monthling (LO)	11
Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0
Excepted quantities (EQ)	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D

GB

Printing date 04.07.2022

Version number 34 (replaces version 33)

Revision: 30.03.2022

#### Trade name: DUPLI-COLOR PROFI DEGREASER SPRAY 400 ML

	(Contd. of page 8)
· IMDG · Limited quantities (LQ)	IL
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

#### SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

 $\cdot$  Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

 $\cdot$  Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· LIST OF SUBSTANCES SUBJECT TO AUTHORISATION (UK ANNEX XIV)

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas.

- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing SDS: R&D legislation and regulatory advisor

· Contact: e-mail: sds-nl@european-aerosols.com

• Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

*PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative* 

(Contd. on page 10)

Page 10/10

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.07.2022

Version number 34 (replaces version 33)

Revision: 30.03.2022

#### Trade name: DUPLI-COLOR PROFI DEGREASER SPRAY 400 ML

(Contd. of page 9)

Flam. Gas 1A: Flammable gases – Category 1A Aerosol 1: Aerosols – Category 1 Press. Gas (Comp.): Gases under pressure – Compressed gas Flam. Liq. 2: Flammable liquids – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 • \* Data compared to the previous version altered.

GB