

Page 1/10

Safety data sheet according to 1907/2006/EC, Article 31

Version number 5 (replaces version 4) Printing date 05.05.2022 Revision: 05.05.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: NICRO Thermocup 1200 Aerosol
- · Article number: 302169, 302152alt, 381799alt, Z-00-1200-40
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC9a Coatings and paints, thinners, paint removers
- · Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

- · Application of the substance / the mixture Coating
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

European Aerosols GmbH*

Kurt Vogelsang Strasse 6

D-74855 Haßmersheim

Tel.: +49 (0) 6266 750

e-mail: sds-de@european-aerosols.com

- *Formerly known as Motip Dupli GmbH
- · Further information obtainable from: Department Product Safety
- · 1.4 Emergency telephone number:

Tel.:+49 6266-75-310

Fax +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

UK:

Public emergeny phone no: 111

Only for healthcare professionals: 0344 892 0111

Poison center if childs have been poisened: 01 809 2166 (8:00 am - 10:00 pm, 7 days)

Only for healthcare professionals: 01 809 2566 (24 h / 7 days)

Tox Info Suisse 145 (24-h-emergency number)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. Aerosol 1



Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

Printing date 05.05.2022 Version number 5 (replaces version 4) Revision: 05.05.2022

Trade name: NICRO Thermocup 1200 Aerosol

(Contd. of page 1)



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms







GHS02

GHS07

GHSO

- · Signal word Danger
- · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated light

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

· Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 64742-49-0 EINECS: 265-151-9 Index number: 649-328-00-1 Reg.nr.: 01-2119475133-43 Naphtha (petroleum), hydrotreated light

🅸 Flam. Liq. 2, H225

& Asp. Tox. 1, H304

📤 Aquatic Chronic 2, H411

Skin Irrit. 2, H315; STOT SE 3, H336

25-<50%

(Contd. on page 3)

Printing date 05.05.2022 Version number 5 (replaces version 4) Revision: 05.05.2022

Trade name: NICRO Thermocup 1200 Aerosol

CAS: 74-98-6	propane	(Contd. of page 2 12.5-<20%
EINECS: 200-827-9	Flam. Gas 1A, H220	_
Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	Press. Gas (Comp.), H280	
CAS: 106-97-8	butane (containing < 0,1 % butadiene (203-450-8))	12.5-<20%
EINECS: 203-448-7 Index number: 601-004-00-0	Flam. Gas 1A, H220 Press. Gas (Comp.), H280	
Reg.nr.: 01-2119474691-32		
CAS: 109-87-5	dimethoxymethane	12.5-<20%
EINECS: 203-714-2 Reg.nr.: 01-2119664781-31	ⓑ Flam. Liq. 2, H225	
CAS: 75-28-5	isobutane (containing < 0,1 % butadiene (203-450-8))	5-<10%
EINECS: 200-857-2	Flam. Gas 1A, H220	
Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	Press. Gas (Comp.), H280	
CAS: 7440-50-8	copper	5-<10%
EINECS: 231-159-6 Reg.nr.: 01-2119480154-42	♦ Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10)	_
	♠ Acute Tox. 4, H302	
CAS: 7429-90-5	aluminium powder (stabilised)	<2.5%
EINECS: 231-072-3	♦ Flam. Sol. 1, H228; Water-react. 2, H261	_
Index number: 013-002-00-1		
Reg.nr.: 01-2119529243-45		

· Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply. For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire extinguishing methods suitable to surrounding conditions.

- 5.2 Special hazards arising from the substance or mixture

 During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.

(Contd. on page 4)

Printing date 05.05.2022 Version number 5 (replaces version 4) Revision: 05.05.2022

Trade name: NICRO Thermocup 1200 Aerosol

Wear protective equipment. Keep unprotected persons away. (Contd. of page 3)

Keep away from ignition sources.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane (containing < 0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm

Long-term value: $1450~mg/m^3$, 600~ppm

Carc (if more than 0.1% of buta-1.3-diene)

109-87-5 dimethoxymethane

WEL Short-term value: 3950 mg/m³, 1250 ppm

Long-term value: 3160 mg/m³, 1000 ppm

7429-90-5 aluminium powder (stabilised)

WEL Long-term value: 10* 4** mg/m³

*inhalable dust ** respirable dust

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

(Contd. on page 5)

GB

Printing date 05.05.2022 Version number 5 (replaces version 4) Revision: 05.05.2022

Trade name: NICRO Thermocup 1200 Aerosol

· Respiratory protection:

(Contd. of page 4)



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· Hand protection



Protective gloves

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42-480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· Eye/face protection Not required.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:

Aerosol

Dark grey
Characteristic
Not determined.

Undetermined.

· Boiling point or initial boiling point and boiling

range Not applicable, as aerosol.
• Flammability Not applicable.

· Lower and upper explosion limit

Lower: 1.5 Vol % *· Upper:* 19.9 Vol %

· Flash point: Not applicable, as aerosol.

Ignition temperature:
 Decomposition temperature:
 Not determined.

• pH Mixture is non-soluble (in water).

· Viscosity:

Kinematic viscosity
 Dynamic:
 Not determined.
 Not determined.

· Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

• Vapour pressure at 20 °C (68 °F): 8300 hPa (6225.5 mm Hg)

· Density and/or relative density

• Density at 20 °C (68 °F): 0.8 g/cm³ (6.7 lbs/gal)
• Relative density Not determined.

(Contd. on page 6)

Printing date 05.05.2022 Version number 5 (replaces version 4) Revision: 05.05.2022

Trade name: NICRO Thermocup 1200 Aerosol

	(Contd. of page
· Vapour density	Not determined.
9.2 Other information	
· Appearance:	
· Form:	Aerosol
Important information on protection of heal	th and
environment, and on safety.	
Explosive properties:	Not determined.
Solvent content:	
Organic solvents:	83.1 %
· VOC (EC)	
· VOC-EU%	
· Solids content:	31.4 %
· Change in condition	
· Evaporation rate	Not applicable.
Information with regard to physical hazard o	classes
Explosives	Void
· Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised container:
	May burst if heated.
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flamm	able
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
· Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

LD/LC50	values	relevant	for cla	assification:

109-87-5 dimethoxymethane		
Oral	LD50	6423 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rab) (OECD 402)
	LC50 / 96 h	>1000 mg/l (fish) (Oncorhynchus mykiss)

(Contd. on page 7)

Printing date 05.05.2022 Version number 5 (replaces version 4) Revision: 05.05.2022

Trade name: NICRO Thermocup 1200 Aerosol

(Contd. of page 6)

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

109-87-5 dimethoxymethane

EC50 / 48 h > 1200 mg/l (daphnia magna) (Daphnia magna)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS

· IMDG AEROSOLS, MARINE POLLUTANT

· IATA AEROSOLS, flammable

(Contd. on page 8)

Printing date 05.05.2022 Version number 5 (replaces version 4) Revision: 05.05.2022

Trade name: NICRO Thermocup 1200 Aerosol

	(Contd. of pag
· 14.3 Transport hazard class(es)	
· ADR	
Y 2	
· Class	2 5F Gases.
· Label	2.1
· IMDG	
· Class	2.1 Gases.
Label	2.1
· IATA	
· Class	2.1 Gases.
· Label	2.1
· 14.4 Packing group · ADR, IMDG, IATA	not regulated
14.5 Environmental hazards:	
· Marine pollutant:	Yes Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Gases.
· Hazard identification number (Kemler code):	-
EMS Number:	F- D , S - U
· Stowage Code	SW1 Protected from sources of heat.
· Segregation Code	SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity abo 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre:
	Segregation as for class 9. Stow "separated from" class except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class
· 14.7 Maritime transport in bulk according to IM instruments	
Transport/Additional information:	* K
· ADR	
· ADR · Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
· · · · · · · · · · · · · · · · · · ·	Not permitted as Excepted Quantity

Printing date 05.05.2022 Version number 5 (replaces version 4) Revision: 05.05.2022

Trade name: NICRO Thermocup 1200 Aerosol

	(Contd. of page 8
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	IL
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· UN ''Model Regulation'':	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H228 Flammable solid.

H261 In contact with water releases flammable gases.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 10)

Version number 5 (replaces version 4) Revision: 05.05.2022 Printing date 05.05.2022

Trade name: NICRO Thermocup 1200 Aerosol

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Sol. 1: Flammable solids – Category 1

Water-react. 2: Substances and mixtures which in contact with water emit flammable gases - Category 2

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

* Data compared to the previous version altered.

(Contd. of page 9)