

Tehničke informacije disperzijske boje za popravke



Disperzijska boja za popravak služi za čišćenje prljavih površina poput zidova i stropova. Primjenjiva je za mrlje uzrokovane masnoćom, nikotinom, čađom i vodom, kao i mrljama insekata, kave, katrana i pastela.

Prikladno je za upotrebu na površinama poput polistirena, tapeta, starih zidnih boja i žbuke.

Kvaliteta i svojstva

- Jaka moć pokrivanja
- Bez neugodnih mirisa
- Na bazi vode
- Vrlo dobra učinkovitost (do 1 m²/ limenka spreja)
- Odličan učinak izolacije
- Uporaba u unutarnjim i vanjskim prostorima
- Premaziv sa disperzijskim bojama
- Bijela mat nijansa

Physical and chemical data

- **Basis of the binder:** Acrylic dispersion
- **Colour:** white mat
- **Smell:** odourless
- **Degree of gloss (at measurement angle 60° acc. to DIN 67530):**
mat: approx. 30 gloss units
- **Efficiency:**
Depending on consistence and colour of the ground: 200 ml are sufficient for up to 1 m².
- **Drying time (at 20°C, 55% relative air humidity):**
Dust-dry: after approx. 30 minutes
Dry to touch: after approx. 40 minutes
Recoatable: after approx. 2 hours
The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.
- **Temperature-resistant:** approx. 90 °C
- **Storage stability:**
Durability 24 months, if appropriate storage provided (temperature 8°-30°C, relative air humidity 30-75%)
- **Size:** Maximum nominal volume, aerosol can 200 ml

Okoliš i označavanje

Ekološki prihvatljivo: European Aerosols proizvodi su u potpunosti (100%) bez teških metala. Kape i ambalaža su izrađene od recikliranog materijala.

Odlaganje: Reciklirati i odlagati u za to predviđene spremnike samo u potpunosti prazne limenke. Limenke koje nisu prazne trebaju se zbrinuti kao "poseban otpad".

Obilježavanje/označavanje: Svi proizvodi proizvedeni u European Aerosols u skladu su sa propisima o označavanju prema direktivi 1999/45 / EG. Svi aerosoli odgovaraju TRGS 200 i TRG300 kao i aerosol direktivi 75/324/EWG u važećoj verziji.

Uputstva za upotrebu

Većina DUPLI-COLOR boja u spreju imaju takozvani zaštitni prsten ili sigurnosnu kapu kako bi se izbjegla neovlaštena upotreba. Prije upotrebe pregledati odgovarajuće savjete na poklopcu ili na naljepnici.

Prije upotrebe pažljivo pročitati upute i upozorenja na naljepnici.

Application

- Before use, shake the can for 2 minutes.
- The surface has to be clean and dry.
- Drily brush water streaks, remove salt efflorescences.
- Initially test spray.
- Apply from a distance of approx. 25 cm several thin cross-coats.
- To increase the insulating effect, let surfaces dry.
- For difficult spots, repeat application if necessary.
- Recoatable with dispersion colours. Protect from frost.

While using dispersion repair paint, a slight bleeding in the insulating layers may occur. If this is the case, please check the insulating effect before applying the final coating. The final insulating effect is reached after complete film formation and after it has been cured. Before applying non-insulating top coats, plan 24 hours waiting time.

As of: August 31, 2015

This release replaces all eventually earlier issued versions.

Datum ispisa: 03.05.2024